

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	05 Hour 33 Min 10 Sec
Total Counter :	1050516	Total Running Time :	2951 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.69	kN	No		
HEP :	25.0 %	37.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.36	kN	Yes 15	Times	
Ref :		29.76	kN			
LCP :	2.0 %	29.17	kN	Yes 15	Times	
LEP :	25.0 %	22.32	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.83	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.08	kN	Min :	3.71	kN	Punch NO.;	25
SD :	4.20	%	Max :	4.50	kN	Punch NO.;	33
Mean Main Pressure :	29.14	kN	Min :	26.76	kN	Punch NO.;	25
SD :	3.60	%	Max :	31.67	kN	Punch NO.;	33
Filling Depth :	Increase ;	151	Times	Decrease ;	164	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.91	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	5
Lower Punch :	Average ;	0.39	kN		
	Max ;	0.91	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1050516	Tablets			
A.W.C Counter :	1029008	Tablets			
HEP :	136 (0.0%)	Tablets	LEP :	1087 (0.1%)	Tablets
GOOD :	1027785 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510240
Print Interval :	50000 Tablets	Running Time :	05 Hour 33 Min 10 Sec
Total Counter :	1050516	Total Running Time :	2951 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	25	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.37	kN	No		
HEP :	25.0 %	36.89	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	30.10	kN	Yes	15	Times
Ref :		29.51	kN			
LCP :	2.0 %	28.92	kN	Yes	15	Times
LEP :	25.0 %	22.13	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.66	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.25	kN	Min :	3.90	kN	Punch NO.;	75
SD :	4.80	%	Max :	4.94	kN	Punch NO.;	67
Mean Main Pressure :	29.78	kN	Min :	27.53	kN	Punch NO.;	9
SD :	3.90	%	Max :	32.57	kN	Punch NO.;	67
Filling Depth :	Increase ;	69	Times	Decrease ;	78	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.75	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.85	mm	Current Cam :	Cam B	
Main Air pressure :	0.753	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	5
Lower Punch :	Average ;	0.39	kN		
	Max ;	0.89	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1050516	Tablets			
A.W.C Counter :	1029008	Tablets			
HEP :	136 (0.0%)	Tablets	LEP :	1087 (0.1%)	Tablets
GOOD :	1027785 (99.9%)	Tablets			