

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510140
Print Interval :	50000 Tablets	Running Time :	00 Hour 04 Min 30 Sec
Total Counter :	11314	Total Running Time :	2961 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.30	kN	No		
HEP :	25.0 %	36.83	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.05	kN	Yes 15	Times	
Ref :		29.46	kN			
LCP :	2.0 %	28.87	kN	Yes 15	Times	
LEP :	25.0 %	22.10	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.62	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.62	kN	Min :	3.31	kN	Punch NO.;	59
		3.70	%	Max :	3.92	kN	Punch NO.;	39
Mean Main Pressure :	SD :	29.38	kN	Min :	26.06	kN	Punch NO.;	59
		3.60	%	Max :	31.54	kN	Punch NO.;	46
Filling Depth :	Increase ;	0	Times	Decrease ;	2	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.24	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.770	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	21
Lower Punch :	Average ;	0.32	kN		
	Max ;	0.67	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	11314	Tablets			
A.W.C Counter :	7837	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	7837 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510140
Print Interval :	50000 Tablets	Running Time :	00 Hour 04 Min 30 Sec
Total Counter :	11314	Total Running Time :	2961 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	59	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.58	kN	No		
HEP :	25.0 %	36.13	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.48	kN	Yes 15	Times	
Ref :		28.91	kN			
LCP :	2.0 %	28.33	kN	Yes 15	Times	
LEP :	25.0 %	21.68	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.23	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.72	kN	Min :	3.24	kN	Punch NO.;	17
		4.30	%	Max :	4.00	kN	Punch NO.;	48
Mean Main Pressure :	SD :	28.79	kN	Min :	25.98	kN	Punch NO.;	17
		3.70	%	Max :	30.83	kN	Punch NO.;	48
Filling Depth :	Increase ;	2	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.75	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.30	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.770	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	21
Lower Punch :	Average ;	0.32	kN		
	Max ;	0.67	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	11314	Tablets			
A.W.C Counter :	7837	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	7837 (100.0%)	Tablets			