

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2510140
Print Interval :	50000 Tablets	Running Time :	08 Hour 26 Min 21 Sec
Total Counter :	1550956	Total Running Time :	2969 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.20	kN	No		
HEP :	25.0 %	38.65	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.54	kN	Yes 15	Times	
Ref :		30.92	kN			
LCP :	2.0 %	30.30	kN	Yes 15	Times	
LEP :	25.0 %	23.19	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.65	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.76	kN	Min :	3.47	kN	Punch NO.;	69
		3.90	%	Max :	4.08	kN	Punch NO.;	77
Mean Main Pressure :	SD :	31.55	kN	Min :	29.46	kN	Punch NO.;	47
		3.40	%	Max :	34.13	kN	Punch NO.;	28
Filling Depth :	Increase ;	91	Times	Decrease ;	117	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.750	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	8
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.44	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1550956	Tablets			
A.W.C Counter :	1542484	Tablets			
HEP :	23 (0.0%)	Tablets	LEP :	331 (0.0%)	Tablets
GOOD :	1542130 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	ms88737	Batch NO. :	KQM2510140
Print Interval :	50000 Tablets	Running Time :	08 Hour 26 Min 21 Sec
Total Counter :	1550956	Total Running Time :	2969 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.48	kN	No		
HEP :	25.0 %	37.96	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.98	kN	Yes 15	Times	
Ref :		30.37	kN			
LCP :	2.0 %	29.76	kN	Yes 15	Times	
LEP :	25.0 %	22.78	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.26	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.73	kN	Min :	3.38	kN	Punch NO.;	37
		3.90	%	Max :	4.14	kN	Punch NO.;	18
Mean Main Pressure :	SD :	30.43	kN	Min :	27.61	kN	Punch NO.;	37
		3.20	%	Max :	32.69	kN	Punch NO.;	28
Filling Depth :	Increase ;	141	Times	Decrease ;	150	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.75	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.750	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.22	kN	Max Punch ;	25
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.44	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1550956	Tablets			
A.W.C Counter :	1542484	Tablets			
HEP :	23 (0.0%)	Tablets	LEP :	331 (0.0%)	Tablets
GOOD :	1542130 (100.0%)	Tablets			