

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	00 Hour 50 Min 35 Sec
Total Counter :	154818	Total Running Time :	2976 Hour 30 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.72	kN	No		
HEP :	25.0 %	36.27	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.59	kN	Yes 15	Times	
Ref :		29.01	kN			
LCP :	2.0 %	28.43	kN	Yes 15	Times	
LEP :	25.0 %	21.76	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.31	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.51	kN	Min :	3.15	kN	Punch NO.;	17
SD :	4.00	%	Max :	3.81	kN	Punch NO.;	1
Mean Main Pressure :	28.65	kN	Min :	25.85	kN	Punch NO.;	17
SD :	4.00	%	Max :	31.19	kN	Punch NO.;	1
Filling Depth :	Increase ; 18	Times	Decrease ; 10	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.28	mm	Current Cam :	Cam B	
Main Air pressure :	0.747	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.22	kN	Max Punch ;	40
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.45	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	154818	Tablets			
A.W.C Counter :	149286	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	149285 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	00 Hour 50 Min 35 Sec
Total Counter :	154818	Total Running Time :	2976 Hour 30 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.28	kN	No		
HEP :	25.0 %	35.85	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.25	kN	Yes 15	Times	
Ref :		28.68	kN			
LCP :	2.0 %	28.10	kN	Yes 15	Times	
LEP :	25.0 %	21.51	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.07	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.64	kN	Min :	3.36	kN	Punch NO.;	49
		4.20	%	Max :	4.03	kN	Punch NO.;	23
Mean Main Pressure :	SD :	28.79	kN	Min :	26.30	kN	Punch NO.;	9
		3.80	%	Max :	31.20	kN	Punch NO.;	23
Filling Depth :	Increase ;	10	Times	Decrease ;	15	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.74	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.34	mm	Current Cam :	Cam B	
Main Air pressure :	0.747	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.22	kN	Max Punch ;	11
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.45	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	154818	Tablets			
A.W.C Counter :	149286	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	149285	Tablets			
	(100.0%)				