

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	01 Hour 23 Min 14 Sec
Total Counter :	254900	Total Running Time :	2977 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.10	kN	No		
HEP :	25.0 %	36.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.89	kN	Yes	15	Times
Ref :		29.31	kN			
LCP :	2.0 %	28.72	kN	Yes	15	Times
LEP :	25.0 %	21.98	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.56	kN	Min :	3.22	kN	Punch NO.;	13
SD :	3.90	%	Max :	3.88	kN	Punch NO.;	41
Mean Main Pressure :	29.43	kN	Min :	26.72	kN	Punch NO.;	9
SD :	3.80	%	Max :	31.78	kN	Punch NO.;	62
Filling Depth :	Increase ;	30	Times	Decrease ;	13	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.91	mm
Filling Depth :	3.72	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.752	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.22	kN	Max Punch ;	40
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.43	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	254900	Tablets			
A.W.C Counter :	249365	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	249364 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	01 Hour 23 Min 14 Sec
Total Counter :	254900	Total Running Time :	2977 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.28	kN	No		
HEP :	25.0 %	35.85	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.25	kN	Yes	15	Times
Ref :		28.68	kN			
LCP :	2.0 %	28.10	kN	Yes	15	Times
LEP :	25.0 %	21.51	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.07	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.54	kN	Min :	3.16	kN	Punch NO.;	51
SD :	4.40	%	Max :	3.89	kN	Punch NO.;	10
Mean Main Pressure :	28.43	kN	Min :	25.41	kN	Punch NO.;	52
SD :	4.30	%	Max :	31.28	kN	Punch NO.;	18
Filling Depth :	Increase ;	20	Times	Decrease ;	25	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.74	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.34	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.752	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.21	kN	Max Punch ;	11
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.43	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	254900	Tablets			
A.W.C Counter :	249365	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	249364 (100.0%)	Tablets			