

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	vy190186	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	03 Hour 33 Min 50 Sec
Total Counter :	655144	Total Running Time :	2979 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	33	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.25	kN	No		
HEP :	25.0 %	35.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.22	kN	Yes 15	Times	
Ref :		28.65	kN			
LCP :	2.0 %	28.08	kN	Yes 15	Times	
LEP :	25.0 %	21.49	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.83	kN	Min :	3.43	kN	Punch NO.;	17
SD :	3.90	%	Max :	4.20	kN	Punch NO.;	67
Mean Main Pressure :	28.50	kN	Min :	25.49	kN	Punch NO.;	22
SD :	3.70	%	Max :	30.65	kN	Punch NO.;	67
Filling Depth :	Increase ;	110	Times	Decrease ;	67	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.99	mm
Filling Depth :	3.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.720	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	29
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.46	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	655144	Tablets			
A.W.C Counter :	647546	Tablets			
HEP :	329 (0.1%)	Tablets	LEP :	175 (0.0%)	Tablets
GOOD :	647042 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	vy190186	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	03 Hour 33 Min 50 Sec
Total Counter :	655144	Total Running Time :	2979 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.74	kN	No		
HEP :	25.0 %	37.25	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	30.40	kN	Yes	15	Times
Ref :		29.80	kN			
LCP :	2.0 %	29.20	kN	Yes	15	Times
LEP :	25.0 %	22.35	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.79	kN	Min :	3.41	kN	Punch NO.;	75
SD :	5.20	%	Max :	4.19	kN	Punch NO.;	41
Mean Main Pressure :	30.04	kN	Min :	27.25	kN	Punch NO.;	75
SD :	4.40	%	Max :	32.13	kN	Punch NO.;	48
Filling Depth :	Increase ;	60	Times	Decrease ;	64	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.74	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.43	mm	Current Cam :	Cam B	
Main Air pressure :	0.720	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	29
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.47	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	655144	Tablets			
A.W.C Counter :	647546	Tablets			
HEP :	329 (0.1%)	Tablets	LEP :	175 (0.0%)	Tablets
GOOD :	647042 (99.9%)	Tablets			