

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	yd98913	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	04 Hour 39 Min 04 Sec
Total Counter :	855234	Total Running Time :	2980 Hour 18 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	12	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.03	kN	No		
HEP :	25.0 %	33.68	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.49	kN	Yes 15	Times	
Ref :		26.95	kN			
LCP :	2.0 %	26.41	kN	Yes 15	Times	
LEP :	25.0 %	20.21	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.69	kN	Min :	3.33	kN	Punch NO.;	71
		4.20	%	Max :	4.10	kN	Punch NO.;	20
Mean Main Pressure :	SD :	26.97	kN	Min :	24.29	kN	Punch NO.;	30
		4.20	%	Max :	29.66	kN	Punch NO.;	20
Filling Depth :	Increase ;	138	Times	Decrease ;	89	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.99	mm
Filling Depth :	3.32	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	14
Lower Punch :	Average ;	0.27	kN		
	Max ;	0.61	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	855234	Tablets			
A.W.C Counter :	847162	Tablets			
HEP :	332 (0.0%)	Tablets	LEP :	428 (0.1%)	Tablets
GOOD :	846402 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	yd98913	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	04 Hour 39 Min 04 Sec
Total Counter :	855234	Total Running Time :	2980 Hour 18 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	34.05	kN	No		
HEP :	25.0 %	32.74	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.72	kN	Yes 15	Times	
Ref :		26.19	kN			
LCP :	2.0 %	25.67	kN	Yes 15	Times	
LEP :	25.0 %	19.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.34	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.71	kN	Min :	3.20	kN	Punch NO.;	17
SD :	4.80	%	Max :	4.18	kN	Punch NO.;	42
Mean Main Pressure :	26.31	kN	Min :	23.01	kN	Punch NO.;	17
SD :	4.40	%	Max :	28.68	kN	Punch NO.;	42
Filling Depth :	Increase ;	100	Times	Decrease ;	93	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.74	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.94	mm
Filling Depth :	3.42	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.748	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	11
Lower Punch :	Average ;	0.27	kN		
	Max ;	0.61	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	855234	Tablets			
A.W.C Counter :	847162	Tablets			
HEP :	332 (0.0%)	Tablets	LEP :	428 (0.1%)	Tablets
GOOD :	846402 (99.9%)	Tablets			