

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	08 Hour 59 Min 55 Sec
Total Counter :	1655678	Total Running Time :	2984 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	35.73	kN	No		
HEP :	25.0 %	34.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.03	kN	Yes 15	Times	
Ref :		27.48	kN			
LCP :	2.0 %	26.93	kN	Yes 15	Times	
LEP :	25.0 %	20.61	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.62	kN	Min :	3.39	kN	Punch NO.;	17
SD :	3.80	%	Max :	3.94	kN	Punch NO.;	2
Mean Main Pressure :	27.58	kN	Min :	24.88	kN	Punch NO.;	9
SD :	4.00	%	Max :	29.88	kN	Punch NO.;	20
Filling Depth :	Increase ;	223	Times	Decrease ;	159	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.69	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.31	mm
Main Upper Punch Position ;	2.69	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.99	mm
Filling Depth :	3.42	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.26	kN	Max Punch ;	12
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.42	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1655678	Tablets			
A.W.C Counter :	1645567	Tablets			
HEP :	334 (0.0%)	Tablets	LEP :	469 (0.0%)	Tablets
GOOD :	1644764 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510340
Print Interval :	50000 Tablets	Running Time :	08 Hour 59 Min 55 Sec
Total Counter :	1655678	Total Running Time :	2984 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	33.62	kN	No		
HEP :	25.0 %	32.33	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	26.38	kN	Yes	15	Times
Ref :		25.86	kN			
LCP :	2.0 %	25.35	kN	Yes	15	Times
LEP :	25.0 %	19.40	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	18.11	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.56	kN	Min :	3.16	kN	Punch NO.;	15
SD :	4.30	%	Max :	3.93	kN	Punch NO.;	57
Mean Main Pressure :	26.24	kN	Min :	23.34	kN	Punch NO.;	15
SD :	4.40	%	Max :	29.09	kN	Punch NO.;	57
Filling Depth :	Increase ;	459	Times	Decrease ;	454	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.74	mm			
Main Lower Punch Position ;	3.68	mm	Main Thickness ;	0.94	mm
Filling Depth :	3.37	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	11
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.42	kN	Max Punch ;	9
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1655678	Tablets			
A.W.C Counter :	1645567	Tablets			
HEP :	334 (0.0%)	Tablets	LEP :	469 (0.0%)	Tablets
GOOD :	1644764 (100.0%)	Tablets			