

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	04 Hour 21 Min 59 Sec
Total Counter :	800374	Total Running Time :	2994 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	21	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	44.46	kN	No		
HEP :	25.0 %	42.75	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.89	kN	Yes 15	Times	
Ref :		34.20	kN			
LCP :	2.0 %	33.52	kN	Yes 15	Times	
LEP :	25.0 %	25.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.94	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.87	kN	Min :	3.44	kN	Punch NO.;	43
SD :	6.00	%	Max :	4.32	kN	Punch NO.;	32
Mean Main Pressure :	33.98	kN	Min :	30.69	kN	Punch NO.;	62
SD :	5.00	%	Max :	37.28	kN	Punch NO.;	32
Filling Depth :	Increase ;	325	Times	Decrease ;	303	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.52	mm	Main Thickness ;	0.82	mm
Filling Depth :	4.72	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.730	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.23	kN	Max Punch ;	43
Lower Punch :	Average ;	0.39	kN		
	Max ;	0.86	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	800374	Tablets			
A.W.C Counter :	780998	Tablets			
HEP :	75 (0.0%)	Tablets	LEP :	275 (0.0%)	Tablets
GOOD :	780648 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	04 Hour 21 Min 59 Sec
Total Counter :	800374	Total Running Time :	2994 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	24	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.95	kN	No		
HEP :	25.0 %	38.41	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	31.35	kN	Yes	15	Times
Ref :		30.73	kN			
LCP :	2.0 %	30.12	kN	Yes	15	Times
LEP :	25.0 %	23.05	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	21.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.78	kN	Min :	3.45	kN	Punch NO.;	8
SD :	3.30	%	Max :	4.05	kN	Punch NO.;	38
Mean Main Pressure :	31.34	kN	Min :	28.90	kN	Punch NO.;	6
SD :	2.80	%	Max :	33.07	kN	Punch NO.;	19
Filling Depth :	Increase ;	64	Times	Decrease ;	70	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	4.00	mm	Pre Thickness ;	1.30	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	0.80	mm
Filling Depth :	3.44	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.730	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.22	kN	Max Punch ;	24
Lower Punch :	Average ;	0.39	kN		
	Max ;	0.86	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	800374	Tablets			
A.W.C Counter :	781075	Tablets			
HEP :	75 (0.0%)	Tablets	LEP :	275 (0.0%)	Tablets
GOOD :	780725 (100.0%)	Tablets			