

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	vy190186	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	07 Hour 30 Min 57 Sec
Total Counter :	1400710	Total Running Time :	2997 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.30	kN	No		
HEP :	25.0 %	39.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	32.40	kN	Yes 15	Times	
Ref :		31.77	kN			
LCP :	2.0 %	31.13	kN	Yes 15	Times	
LEP :	25.0 %	23.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.43	kN	Min :	3.85	kN	Punch NO.;	62
SD :	6.00	%	Max :	5.13	kN	Punch NO.;	53
Mean Main Pressure :	32.19	kN	Min :	29.61	kN	Punch NO.;	19
SD :	4.00	%	Max :	35.37	kN	Punch NO.;	53
Filling Depth :	Increase ;	462	Times	Decrease ;	444	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.49	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.36	kN	Max Punch ;	23
Lower Punch :	Average ;	0.41	kN		
	Max ;	1.64	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1400710	Tablets			
A.W.C Counter :	1368244	Tablets			
HEP :	195 (0.0%)	Tablets	LEP :	669 (0.0%)	Tablets
GOOD :	1367380 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	vy190186	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	07 Hour 30 Min 57 Sec
Total Counter :	1400710	Total Running Time :	2997 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.29	kN	No		
HEP :	25.0 %	35.85	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.26	kN	Yes 15	Times	
Ref :		28.68	kN			
LCP :	2.0 %	28.11	kN	Yes 15	Times	
LEP :	25.0 %	21.51	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.08	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.19	kN	Min :	3.64	kN	Punch NO.;	2
SD :	4.40	%	Max :	4.78	kN	Punch NO.;	13
Mean Main Pressure :	28.69	kN	Min :	24.82	kN	Punch NO.;	2
SD :	3.80	%	Max :	31.67	kN	Punch NO.;	13
Filling Depth :	Increase ;	130	Times	Decrease ;	112	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	203280	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.70	mm			
Pre Lower Punch Position ;	3.90	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.70	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.59	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.27	kN		
	Max ;	0.35	kN	Max Punch ;	23
Lower Punch :	Average ;	0.41	kN		
	Max ;	1.64	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1400710	Tablets			
A.W.C Counter :	1368244	Tablets			
HEP :	195 (0.0%)	Tablets	LEP :	669 (0.0%)	Tablets
GOOD :	1367380 (99.9%)	Tablets			