

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	09 Hour 37 Min 05 Sec
Total Counter :	1850990	Total Running Time :	3000 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	84	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	41.18	kN	No		
HEP :	25.0 %	39.59	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	32.31	kN	Yes	15	Times
Ref :		31.67	kN			
LCP :	2.0 %	31.04	kN	Yes	15	Times
LEP :	25.0 %	23.76	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	22.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.18	kN	Min :	3.74	kN	Punch NO.;	14
SD :	5.70	%	Max :	4.92	kN	Punch NO.;	32
Mean Main Pressure :	31.81	kN	Min :	28.75	kN	Punch NO.;	40
SD :	4.10	%	Max :	35.61	kN	Punch NO.;	32
Filling Depth :	Increase ;	574	Times	Decrease ;	532	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.84	mm
Filling Depth :	4.78	mm	Current Cam :	Cam B	
Main Air pressure :	0.751	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.48	kN		
	Max ;	0.59	kN	Max Punch ;	30
Lower Punch :	Average ;	0.48	kN		
	Max ;	1.07	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1850990	Tablets			
A.W.C Counter :	1807454	Tablets			
HEP :	335 (0.0%)	Tablets	LEP :	1174 (0.1%)	Tablets
GOOD :	1805945 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510440
Print Interval :	50000 Tablets	Running Time :	09 Hour 37 Min 05 Sec
Total Counter :	1850990	Total Running Time :	3000 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	74	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	36.81	kN	No		
HEP :	25.0 %	35.39	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.88	kN	Yes 15	Times	
Ref :		28.31	kN			
LCP :	2.0 %	27.75	kN	Yes 15	Times	
LEP :	25.0 %	21.23	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.82	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.98	kN	Min :	3.50	kN	Punch NO.;	67
SD :	5.10	%	Max :	4.45	kN	Punch NO.;	38
Mean Main Pressure :	28.35	kN	Min :	25.53	kN	Punch NO.;	41
SD :	4.50	%	Max :	30.86	kN	Punch NO.;	32
Filling Depth :	Increase ;	389	Times	Decrease ;	357	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.19	mm	Pre Thickness ;	1.19	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.68	mm	Current Cam :	Cam B	
Main Air pressure :	0.751	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.48	kN		
	Max ;	0.59	kN	Max Punch ;	35
Lower Punch :	Average ;	0.48	kN		
	Max ;	1.07	kN	Max Punch ;	1
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1850990	Tablets			
A.W.C Counter :	1807454	Tablets			
HEP :	335 (0.0%)	Tablets	LEP :	1174 (0.1%)	Tablets
GOOD :	1805945 (99.9%)	Tablets			