

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	00 Hour 06 Min 12 Sec
Total Counter :	23602	Total Running Time :	3003 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.77	kN	No		
HEP :	25.0 %	39.20	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	31.99	kN	Yes	15 Times	
Ref :		31.36	kN			
LCP :	2.0 %	30.73	kN	Yes	15 Times	
LEP :	25.0 %	23.52	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	21.95	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.07	kN	Min :	3.57	kN	Punch NO.;	26
SD :	5.60	%	Max :	4.57	kN	Punch NO.;	53
Mean Main Pressure :	31.77	kN	Min :	28.29	kN	Punch NO.;	63
SD :	4.60	%	Max :	34.48	kN	Punch NO.;	9
Filling Depth :	Increase ;	801	Times	Decrease ;	761	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.38	mm	Current Cam :	Cam B	
Main Air pressure :	0.734	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.53	kN		
	Max ;	0.63	kN	Max Punch ;	66
Lower Punch :	Average ;	0.30	kN		
	Max ;	0.82	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	23602	Tablets			
A.W.C Counter :	15591	Tablets			
HEP :	0 (0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	15590 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	00 Hour 06 Min 12 Sec
Total Counter :	23602	Total Running Time :	3003 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	57	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	36.60	kN	No		
HEP :	25.0 %	35.19	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.71	kN	Yes 15	Times	
Ref :		28.15	kN			
LCP :	2.0 %	27.59	kN	Yes 15	Times	
LEP :	25.0 %	21.11	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.71	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.80	kN	Min :	3.10	kN	Punch NO.;	6
SD :	6.70	%	Max :	4.39	kN	Punch NO.;	38
Mean Main Pressure :	27.21	kN	Min :	21.01	kN	Punch NO.;	6
SD :	6.10	%	Max :	30.59	kN	Punch NO.;	38
Filling Depth :	Increase ;	589	Times	Decrease ;	556	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.83	mm	Current Cam :	Cam B	
Main Air pressure :	0.734	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.53	kN		
	Max ;	0.63	kN	Max Punch ;	66
Lower Punch :	Average ;	0.29	kN		
	Max ;	0.82	kN	Max Punch ;	72
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	23602	Tablets			
A.W.C Counter :	15591	Tablets			
HEP :	0 (0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	15590 (100.0%)	Tablets			