

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 16 Sec
Total Counter :	300198	Total Running Time :	3005 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	93	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.80	kN	No		
HEP :	25.0 %	42.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.36	kN	Yes 15	Times	
Ref :		33.69	kN			
LCP :	2.0 %	33.02	kN	Yes 15	Times	
LEP :	25.0 %	25.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.07	kN	Min :	3.56	kN	Punch NO.;	60
SD :	7.10	%	Max :	4.95	kN	Punch NO.;	76
Mean Main Pressure :	33.01	kN	Min :	29.02	kN	Punch NO.;	2
SD :	5.60	%	Max :	37.76	kN	Punch NO.;	76
Filling Depth :	Increase ;	937	Times	Decrease ;	883	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	23	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.11	mm	Current Cam :	Cam B	
Main Air pressure :	0.700	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.57	kN		
	Max ;	0.68	kN	Max Punch ;	26
Lower Punch :	Average ;	0.29	kN		
	Max ;	0.78	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300198	Tablets			
A.W.C Counter :	292175	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	292170 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	01 Hour 18 Min 16 Sec
Total Counter :	300198	Total Running Time :	3005 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	87	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.64	kN	No		
HEP :	25.0 %	36.19	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.53	kN	Yes 15	Times	
Ref :		28.95	kN			
LCP :	2.0 %	28.37	kN	Yes 15	Times	
LEP :	25.0 %	21.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.83	kN	Min :	3.34	kN	Punch NO.;	70
SD :	5.60	%	Max :	4.36	kN	Punch NO.;	19
Mean Main Pressure :	28.66	kN	Min :	24.39	kN	Punch NO.;	74
SD :	5.00	%	Max :	32.02	kN	Punch NO.;	19
Filling Depth :	Increase ;	681	Times	Decrease ;	654	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.700	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.57	kN		
	Max ;	0.68	kN	Max Punch ;	26
Lower Punch :	Average ;	0.29	kN		
	Max ;	0.78	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300198	Tablets			
A.W.C Counter :	292175	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	292170 (100.0%)	Tablets			