

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	02 Hour 25 Min 59 Sec
Total Counter :	550350	Total Running Time :	3006 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.80	kN	No		
HEP :	25.0 %	42.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.36	kN	Yes 15	Times	
Ref :		33.69	kN			
LCP :	2.0 %	33.02	kN	Yes 15	Times	
LEP :	25.0 %	25.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.58	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.98	kN	Min :	3.47	kN	Punch NO.;	67
		6.80	%	Max :	4.57	kN	Punch NO.;	33
Mean Main Pressure :	SD :	31.57	kN	Min :	27.64	kN	Punch NO.;	63
		6.00	%	Max :	35.16	kN	Punch NO.;	33
Filling Depth :	Increase ;	1051	Times	Decrease ;	1003	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.90	mm	Current Cam :	Cam B	
Main Air pressure :	0.747	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.50	kN	Max Punch ;	35
Lower Punch :	Average ;	0.23	kN		
	Max ;	0.70	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550350	Tablets			
A.W.C Counter :	540908	Tablets			
HEP :	39 (0.0%)	Tablets	LEP :	339 (0.1%)	Tablets
GOOD :	540530 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	02 Hour 25 Min 59 Sec
Total Counter :	550350	Total Running Time :	3006 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	67	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.28	kN	No		
HEP :	25.0 %	36.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.04	kN	Yes 15	Times	
Ref :		29.45	kN			
LCP :	2.0 %	28.86	kN	Yes 15	Times	
LEP :	25.0 %	22.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.61	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.92	kN	Min :	3.46	kN	Punch NO.;	17
SD :	4.60	%	Max :	4.33	kN	Punch NO.;	37
Mean Main Pressure :	28.67	kN	Min :	26.03	kN	Punch NO.;	17
SD :	3.90	%	Max :	31.10	kN	Punch NO.;	37
Filling Depth :	Increase ;	813	Times	Decrease ;	783	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.747	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	42	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.41	kN		
	Max ;	0.50	kN	Max Punch ;	35
Lower Punch :	Average ;	0.23	kN		
	Max ;	0.68	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550350	Tablets			
A.W.C Counter :	540908	Tablets			
HEP :	39 (0.0%)	Tablets	LEP :	339 (0.1%)	Tablets
GOOD :	540530 (99.9%)	Tablets			