SEJONG PHARMATECH

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D		Product Name :	PANTO 40 MG,STKQ1B00	
User ID :	sj97904		Batch NO. :	KQM2510540	
Print Interval :	50000 Tablets		Running Time :	03 Hour 07 Min 06 Sec	
Total Counter :	700448	Tablets	Total Running Time :	3006 Hour 53 Min	
Station :	Station 1				

Setting Value

Feeder :	Auto ;		54	%	Manual ;			45	RPM
Filling Cam :			Cam B 4.5-10mm		Cam Range :		Min :	2.50	mm
Target Quantity :			2750000	Tablets			Max :	8.00	mm
Air Pressure Low Limit :			0.400	MPa					
Oil Lubrication :									
Upper Punch Interval Time(S1) ;			50	Min	Supply Time ;			2.0	Sec
Lower Punch Interval Time(S2) ;			20	Min	Supply Time ;			10.0	Sec
Powder Supply Time :			60.0	Sec					
Initial Reject Time :			1	Tablets					
Upper Punch Tightness High Limit :			2.00	kN					
Lower Punch Tightness High Limit :			3.00	kN					
Ejecting Force High Limit :			4.90	kN					
					Stop Condition ;				
HSP :	30.0	%	40.94	kN	No				
HEP :	25.0	%	39.37	kN	Yes	10	Rotations	15	Tablets
HCP :	2.0	%	32.12	kN	Yes	15	Times		
Ref :			31.49	kN					
LCP :	2.0	%	30.86	kN	Yes	15	Times		
LEP :	25.0	%	23.62	kN	Yes	10	Rotations	15	Tablets
LSP :	30.0	%	22.05	kN	No				
SD limit :	45.0	%			Yes				
Pre HSP			40.00	kN	Yes				
Mean Calculation range :	2	Rotations			Calculation Pass :			2	Rotations
Empty Punch No. :	None								

Pressure Data

Mean Pre Pressure :		4.12	kN	Min :	3.67	kN	Punch NO.;	8
	SD :	5.80	%	Max :	4.69	kN	Punch NO.;	71
Mean Main Pressure :		31.88	kN	Min :	28.93	kN	Punch NO.;	6
	SD :	4.60	%	Max :	35.22	kN	Punch NO.;	10
Filling Depth :	Increase ;	1142	Times	Decrease ;	1083	Times		

SEJONG PHARMATECH

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.98	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.740	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.44	kN		
	Max ;	0.53	kN	Max Punch ;	12
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.83	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700448	Tablets			
A.W.C Counter :	687617	Tablets			
HEP :	87 (0.0%)	Tablets	LEP :	430 (0.1%)	Tablets
GOOD :	687100 (99.9%)	Tablets			

SEJONG PHARMATECH

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D		Product Name :	PANTO 40 MG,STKQ1B00	
User ID :	sj97904		Batch NO. :	KQM2510540	
Print Interval :	50000 Tablets		Running Time :	03 Hour 07 Min 06 Sec	
Total Counter :	700448	Tablets	Total Running Time :	3006 Hour 53 Min	
Station :	Station 2				

Setting Value

Feeder :	Auto ;		54	%	Manual ;			45	RPM
Filling Cam :			Cam B 4.5-10mm		Cam Range :		Min :	2.50	mm
Target Quantity :			2750000	Tablets			Max :	8.00	mm
Air Pressure Low Limit :			0.400	MPa					
Oil Lubrication :									
Upper Punch Interval Time(S1) ;			50	Min	Supply Time ;			2.0	Sec
Lower Punch Interval Time(S2) ;			20	Min	Supply Time ;			10.0	Sec
Powder Supply Time :			60.0	Sec					
Initial Reject Time :			1	Tablets					
Upper Punch Tightness High Limit :			2.00	kN					
Lower Punch Tightness High Limit :			3.00	kN					
Ejecting Force High Limit :			4.90	kN					
					Stop Condition ;				
HSP :	30.0	%	36.26	kN	No				
HEP :	25.0	%	34.86	kN	Yes	10	Rotations	15	Tablets
HCP :	2.0	%	28.45	kN	Yes	15	Times		
Ref :			27.89	kN					
LCP :	2.0	%	27.33	kN	Yes	15	Times		
LEP :	25.0	%	20.92	kN	Yes	10	Rotations	15	Tablets
LSP :	30.0	%	19.52	kN	No				
SD limit :	45.0	%			Yes				
Pre HSP			40.00	kN	Yes				
Mean Calculation range :	1	Rotations			Calculation Pass :			1	Rotations
Empty Punch No. :	N								

Pressure Data

Mean Pre Pressure :		3.92	kN	Min :	3.35	kN	Punch NO.;	48
	SD :	6.50	%	Max :	4.55	kN	Punch NO.;	10
Mean Main Pressure :		27.79	kN	Min :	24.31	kN	Punch NO.;	48
	SD :	5.30	%	Max :	31.15	kN	Punch NO.;	19
Filling Depth :	Increase ;	903	Times	Decrease ;	861	Times		

SEJONG PHARMATECH

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.81	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.740	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.43	kN		
	Max ;	0.54	kN	Max Punch ;	30
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.83	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	700448	Tablets			
A.W.C Counter :	687617	Tablets			
HEP :	87 (0.0%)	Tablets	LEP :	430 (0.1%)	Tablets
GOOD :	687100 (99.9%)	Tablets			