

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	04 Hour 57 Min 13 Sec
Total Counter :	1100622	Total Running Time :	3008 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	42.28	kN	No		
HEP :	25.0 %	40.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	33.18	kN	Yes 15	Times	
Ref :		32.53	kN			
LCP :	2.0 %	31.88	kN	Yes 15	Times	
LEP :	25.0 %	24.39	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	22.77	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.57	kN	Min :	4.01	kN	Punch NO.;	57
SD :	5.80	%	Max :	5.35	kN	Punch NO.;	51
Mean Main Pressure :	33.97	kN	Min :	30.84	kN	Punch NO.;	45
SD :	4.00	%	Max :	38.13	kN	Punch NO.;	51
Filling Depth :	Increase ;	1316	Times	Decrease ;	1269	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.24	kN	Max Punch ;	18
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.80	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100622	Tablets			
A.W.C Counter :	1084044	Tablets			
HEP :	201 (0.0%)	Tablets	LEP :	1281 (0.1%)	Tablets
GOOD :	1082562 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	04 Hour 57 Min 13 Sec
Total Counter :	1100622	Total Running Time :	3008 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.63	kN	No		
HEP :	25.0 %	36.19	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.53	kN	Yes	15	Times
Ref :		28.95	kN			
LCP :	2.0 %	28.37	kN	Yes	15	Times
LEP :	25.0 %	21.71	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.26	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.05	kN	Min :	3.33	kN	Punch NO.;	21
SD :	6.00	%	Max :	4.71	kN	Punch NO.;	46
Mean Main Pressure :	29.01	kN	Min :	24.83	kN	Punch NO.;	21
SD :	4.90	%	Max :	32.08	kN	Punch NO.;	46
Filling Depth :	Increase ;	1057	Times	Decrease ;	1008	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	184800	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.04	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.24	kN	Max Punch ;	44
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.80	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1100622	Tablets			
A.W.C Counter :	1084121	Tablets			
HEP :	201 (0.0%)	Tablets	LEP :	1281 (0.1%)	Tablets
GOOD :	1082639 (99.9%)	Tablets			