

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	08 Hour 25 Min 29 Sec
Total Counter :	1801080	Total Running Time :	3012 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	61	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	39.90	kN	No		
HEP :	25.0 %	38.37	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.31	kN	Yes 15	Times	
Ref :		30.69	kN			
LCP :	2.0 %	30.08	kN	Yes 15	Times	
LEP :	25.0 %	23.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.80	kN	Min :	3.26	kN	Punch NO.;	17
		6.80	%	Max :	4.55	kN	Punch NO.;	7
Mean Main Pressure :	SD :	30.05	kN	Min :	26.18	kN	Punch NO.;	17
		6.20	%	Max :	35.38	kN	Punch NO.;	7
Filling Depth :	Increase ;	1752	Times	Decrease ;	1698	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.24	mm	Current Cam :	Cam B	
Main Air pressure :	0.749	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.49	kN		
	Max ;	0.61	kN	Max Punch ;	35
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.85	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1801080	Tablets			
A.W.C Counter :	1775367	Tablets			
HEP :	561 (0.0%)	Tablets	LEP :	2115 (0.1%)	Tablets
GOOD :	1772691 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	08 Hour 25 Min 29 Sec
Total Counter :	1801080	Total Running Time :	3012 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.25	kN	No		
HEP :	25.0 %	35.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.22	kN	Yes 15	Times	
Ref :		28.65	kN			
LCP :	2.0 %	28.08	kN	Yes 15	Times	
LEP :	25.0 %	21.49	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.06	kN	Min :	3.51	kN	Punch NO.;	41
SD :	4.60	%	Max :	4.47	kN	Punch NO.;	70
Mean Main Pressure :	29.00	kN	Min :	25.08	kN	Punch NO.;	41
SD :	4.00	%	Max :	31.26	kN	Punch NO.;	1
Filling Depth :	Increase ;	1542	Times	Decrease ;	1431	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.749	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.48	kN		
	Max ;	0.60	kN	Max Punch ;	31
Lower Punch :	Average ;	0.28	kN		
	Max ;	0.85	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1801080	Tablets			
A.W.C Counter :	1775367	Tablets			
HEP :	561 (0.0%)	Tablets	LEP :	2115 (0.1%)	Tablets
GOOD :	1772691 (99.8%)	Tablets			