

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	08 Hour 39 Min 03 Sec
Total Counter :	1851108	Total Running Time :	3012 Hour 25 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	61	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.73	kN	No		
HEP :	25.0 %	39.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.96	kN	Yes 15	Times	
Ref :		31.33	kN			
LCP :	2.0 %	30.70	kN	Yes 15	Times	
LEP :	25.0 %	23.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.50	kN	Min :	2.51	kN	Punch NO.;	37
SD :	17.30	%	Max :	7.38	kN	Punch NO.;	74
Mean Main Pressure :	35.59	kN	Min :	28.63	kN	Punch NO.;	37
SD :	12.50	%	Max :	50.72	kN	Punch NO.;	74
Filling Depth :	Increase ;	1783	Times	Decrease ;	1733	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.21	mm	Current Cam :	Cam B	
Main Air pressure :	0.754	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.31	kN		
	Max ;	0.57	kN	Max Punch ;	30
Lower Punch :	Average ;	0.26	kN		
	Max ;	0.82	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851108	Tablets			
A.W.C Counter :	1825230	Tablets			
HEP :	565 (0.0%)	Tablets	LEP :	2118 (0.1%)	Tablets
GOOD :	1822547 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	08 Hour 39 Min 03 Sec
Total Counter :	1851108	Total Running Time :	3012 Hour 25 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	37.25	kN	No		
HEP :	25.0 %	35.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.22	kN	Yes 15	Times	
Ref :		28.65	kN			
LCP :	2.0 %	28.08	kN	Yes 15	Times	
LEP :	25.0 %	21.49	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.36	kN	Min :	3.65	kN	Punch NO.;	55
SD :	9.60	%	Max :	7.26	kN	Punch NO.;	37
Mean Main Pressure :	31.01	kN	Min :	26.90	kN	Punch NO.;	55
SD :	6.90	%	Max :	45.40	kN	Punch NO.;	37
Filling Depth :	Increase ;	1558	Times	Decrease ;	1449	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.90	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.754	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	47	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.37	kN		
	Max ;	0.73	kN	Max Punch ;	67
Lower Punch :	Average ;	0.26	kN		
	Max ;	0.82	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851108	Tablets			
A.W.C Counter :	1825230	Tablets			
HEP :	565 (0.0%)	Tablets	LEP :	2118 (0.1%)	Tablets
GOOD :	1822547 (99.9%)	Tablets			