

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	11 Hour 08 Min 24 Sec
Total Counter :	2401498	Total Running Time :	3014 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	61	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.60	kN	No		
HEP :	25.0 %	41.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.21	kN	Yes 15	Times	
Ref :		33.54	kN			
LCP :	2.0 %	32.87	kN	Yes 15	Times	
LEP :	25.0 %	25.16	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.48	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.15	kN	Min :	3.60	kN	Punch NO.;	27
SD :	5.30	%	Max :	4.82	kN	Punch NO.;	12
Mean Main Pressure :	34.00	kN	Min :	29.96	kN	Punch NO.;	27
SD :	5.00	%	Max :	38.46	kN	Punch NO.;	11
Filling Depth :	Increase ;	2138	Times	Decrease ;	2110	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.86	mm	Main Thickness ;	0.86	mm
Filling Depth :	3.88	mm	Current Cam :	Cam B	
Main Air pressure :	0.760	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.45	kN		
	Max ;	0.55	kN	Max Punch ;	25
Lower Punch :	Average ;	0.26	kN		
	Max ;	0.82	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2401498	Tablets			
A.W.C Counter :	2374461	Tablets			
HEP :	588 (0.0%)	Tablets	LEP :	2459 (0.1%)	Tablets
GOOD :	2371414 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	cb83530	Batch NO. :	KQM2510540
Print Interval :	50000 Tablets	Running Time :	11 Hour 08 Min 24 Sec
Total Counter :	2401498	Total Running Time :	3014 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	62	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	10.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	40.00	kN	No		
HEP :	25.0 %	38.47	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	31.39	kN	Yes 15	Times	
Ref :		30.77	kN			
LCP :	2.0 %	30.16	kN	Yes 15	Times	
LEP :	25.0 %	23.08	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	21.54	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.19	kN	Min :	3.69	kN	Punch NO.;	65
SD :	4.70	%	Max :	4.72	kN	Punch NO.;	38
Mean Main Pressure :	30.65	kN	Min :	27.90	kN	Punch NO.;	74
SD :	4.10	%	Max :	33.87	kN	Punch NO.;	38
Filling Depth :	Increase ;	1741	Times	Decrease ;	1623	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.85	mm
Filling Depth :	4.24	mm	Current Cam :	Cam B	
Main Air pressure :	0.760	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.45	kN		
	Max ;	0.56	kN	Max Punch ;	19
Lower Punch :	Average ;	0.26	kN		
	Max ;	0.82	kN	Max Punch ;	40
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2401498	Tablets			
A.W.C Counter :	2374461	Tablets			
HEP :	588 (0.0%)	Tablets	LEP :	2459 (0.1%)	Tablets
GOOD :	2371414 (99.9%)	Tablets			