

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510840
Print Interval :	50000 Tablets	Running Time :	11 Hour 19 Min 04 Sec
Total Counter :	2501598	Total Running Time :	3052 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	43.63	kN	No		
HEP :	25.0 %	41.95	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	34.23	kN	Yes 15	Times	
Ref :		33.56	kN			
LCP :	2.0 %	32.89	kN	Yes 15	Times	
LEP :	25.0 %	25.17	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	23.49	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.28	kN	Min :	2.18	kN	Punch NO.;	66
SD :	1.60	%	Max :	2.36	kN	Punch NO.;	29
Mean Main Pressure :	33.83	kN	Min :	27.58	kN	Punch NO.;	27
SD :	4.10	%	Max :	36.73	kN	Punch NO.;	35
Filling Depth :	Increase ;	797	Times	Decrease ;	685	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	4.42	mm	Current Cam :	Cam B	
Main Air pressure :	0.735	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.32	kN	Max Punch ;	3
Lower Punch :	Average ;	0.22	kN		
	Max ;	0.56	kN	Max Punch ;	22
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2501598	Tablets			
A.W.C Counter :	2493127	Tablets			
HEP :	189 (0.0%)	Tablets	LEP :	1204 (0.0%)	Tablets
GOOD :	2491734 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG,STKQ1B00
User ID :	pb97604	Batch NO. :	KQM2510840
Print Interval :	50000 Tablets	Running Time :	11 Hour 19 Min 04 Sec
Total Counter :	2501598	Total Running Time :	3052 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	34	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	38.44	kN	No		
HEP :	25.0 %	36.97	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	30.16	kN	Yes 15	Times	
Ref :		29.57	kN			
LCP :	2.0 %	28.98	kN	Yes 15	Times	
LEP :	25.0 %	22.18	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.70	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.30	kN	Min :	2.22	kN	Punch NO.;	31
SD :	1.50	%	Max :	2.37	kN	Punch NO.;	25
Mean Main Pressure :	29.59	kN	Min :	23.86	kN	Punch NO.;	27
SD :	4.60	%	Max :	32.71	kN	Punch NO.;	8
Filling Depth :	Increase ;	2363	Times	Decrease ;	2343	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	221760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.20	mm	Pre Thickness ;	1.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.84	mm	Main Thickness ;	0.85	mm
Filling Depth :	3.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.735	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.25	kN		
	Max ;	0.32	kN	Max Punch ;	3
Lower Punch :	Average ;	0.22	kN		
	Max ;	0.56	kN	Max Punch ;	22
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2501598	Tablets			
A.W.C Counter :	2493204	Tablets			
HEP :	189 (0.0%)	Tablets	LEP :	1204 (0.0%)	Tablets
GOOD :	2491811 (99.9%)	Tablets			