

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STSH1A00
User ID :	pb97604	Batch NO. :	HAM2501350
Print Interval :	50000 Tablets	Running Time :	03 Hour 41 Min 11 Sec
Total Counter :	350122	Total Running Time :	3057 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	12.28	kN	No		
HEP :	15.0 %	11.48	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	10.13	kN	Yes 15	Times	
Ref :		9.98	kN			
LCP :	1.5 %	9.83	kN	Yes 15	Times	
LEP :	15.0 %	8.49	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.69	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.10	kN	Min :	2.08	kN	Punch NO.;	31
SD :	0.30	%	Max :	2.12	kN	Punch NO.;	6
Mean Main Pressure :	10.45	kN	Min :	9.70	kN	Punch NO.;	33
SD :	3.10	%	Max :	11.24	kN	Punch NO.;	17
Filling Depth :	Increase ;	361	Times	Decrease ;	369	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.65	mm	Main Thickness ;	2.65	mm
Filling Depth :	8.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.738	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	27
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.18	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350122	Tablets			
A.W.C Counter :	327218	Tablets			
HEP :	1386 (0.4%)	Tablets	LEP :	990 (0.3%)	Tablets
GOOD :	324842 (99.3%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STSH1A00
User ID :	pb97604	Batch NO. :	HAM2501350
Print Interval :	50000 Tablets	Running Time :	03 Hour 41 Min 11 Sec
Total Counter :	350122	Total Running Time :	3057 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	12.19	kN	No		
HEP :	15.0 %	11.40	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	10.06	kN	Yes 15	Times	
Ref :		9.91	kN			
LCP :	1.5 %	9.76	kN	Yes 15	Times	
LEP :	15.0 %	8.42	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.63	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.12	kN	Min :	2.09	kN	Punch NO.;	41
SD :	0.40	%	Max :	2.13	kN	Punch NO.;	2
Mean Main Pressure :	9.95	kN	Min :	9.22	kN	Punch NO.;	31
SD :	2.50	%	Max :	10.56	kN	Punch NO.;	23
Filling Depth :	Increase ;	361	Times	Decrease ;	402	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.85	mm	Main Thickness ;	2.85	mm
Filling Depth :	8.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.738	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	27
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.18	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350122	Tablets			
A.W.C Counter :	327218	Tablets			
HEP :	1386 (0.4%)	Tablets	LEP :	990 (0.3%)	Tablets
GOOD :	324842 (99.3%)	Tablets			