

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	ms88737	Batch NO. :	HAM2501550
Print Interval :	50000 Tablets	Running Time :	05 Hour 46 Min 49 Sec
Total Counter :	550174	Total Running Time :	3074 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	11.89	kN	No		
HEP :	15.0 %	11.12	kN	Yes	10	Rotations 15 Tablets
HCP :	1.5 %	9.81	kN	Yes	15	Times
Ref :		9.67	kN			
LCP :	1.5 %	9.52	kN	Yes	15	Times
LEP :	15.0 %	8.22	kN	Yes	10	Rotations 15 Tablets
LSP :	23.0 %	7.44	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.05	kN	Min :	2.03	kN	Punch NO.;	26
		0.30	%	Max :	2.07	kN	Punch NO.;	2
Mean Main Pressure :	SD :	9.67	kN	Min :	9.13	kN	Punch NO.;	33
		2.20	%	Max :	10.14	kN	Punch NO.;	7
Filling Depth :	Increase ;	1793	Times	Decrease ;	1647	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.70	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.727	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	22
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550174	Tablets			
A.W.C Counter :	548107	Tablets			
HEP :	353 (0.1%)	Tablets	LEP :	375 (0.1%)	Tablets
GOOD :	547379 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	ms88737	Batch NO. :	HAM2501550
Print Interval :	50000 Tablets	Running Time :	05 Hour 46 Min 49 Sec
Total Counter :	550174	Total Running Time :	3074 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	12.46	kN	No		
HEP :	15.0 %	11.65	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	10.29	kN	Yes 15	Times	
Ref :		10.13	kN			
LCP :	1.5 %	9.98	kN	Yes 15	Times	
LEP :	15.0 %	8.61	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.80	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.09	kN	Min :	2.07	kN	Punch NO.;	4
SD :	0.60	%	Max :	2.13	kN	Punch NO.;	7
Mean Main Pressure :	10.21	kN	Min :	9.33	kN	Punch NO.;	21
SD :	3.30	%	Max :	10.81	kN	Punch NO.;	23
Filling Depth :	Increase ;	1946	Times	Decrease ;	1959	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.85	mm	Main Thickness ;	2.85	mm
Filling Depth :	7.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.727	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.14	kN	Max Punch ;	22
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550174	Tablets			
A.W.C Counter :	548107	Tablets			
HEP :	353 (0.1%)	Tablets	LEP :	375 (0.1%)	Tablets
GOOD :	547379 (99.9%)	Tablets			