

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	pb97604	Batch NO. :	HAM2501650
Print Interval :	50000 Tablets	Running Time :	07 Hour 50 Min 46 Sec
Total Counter :	747100	Total Running Time :	3084 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	98	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	11.93	kN	No		
HEP :	15.0 %	11.15	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.84	kN	Yes 15	Times	
Ref :		9.70	kN			
LCP :	1.5 %	9.55	kN	Yes 15	Times	
LEP :	15.0 %	8.24	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.04	kN	Min :	2.02	kN	Punch NO.;	3
		0.30	%	Max :	2.07	kN	Punch NO.;	13
Mean Main Pressure :		9.76	kN	Min :	9.30	kN	Punch NO.;	6
	SD :	2.10	%	Max :	10.18	kN	Punch NO.;	19
Filling Depth :	Increase ;	2183	Times	Decrease ;	2050	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.70	mm	Main Thickness ;	2.70	mm
Filling Depth :	7.89	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.760	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	2
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	46
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	747100	Tablets			
A.W.C Counter :	744139	Tablets			
HEP :	621 (0.1%)	Tablets	LEP :	238 (0.0%)	Tablets
GOOD :	743280 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 500MG STHA1A00
User ID :	pb97604	Batch NO. :	HAM2501650
Print Interval :	50000 Tablets	Running Time :	07 Hour 50 Min 46 Sec
Total Counter :	747100	Total Running Time :	3084 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	98	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	11.58	kN	No		
HEP :	15.0 %	10.82	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.55	kN	Yes 15	Times	
Ref :		9.41	kN			
LCP :	1.5 %	9.27	kN	Yes 15	Times	
LEP :	15.0 %	8.00	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.25	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.07	kN	Min :	2.04	kN	Punch NO.;	7
		0.50	%	Max :	2.10	kN	Punch NO.;	6
Mean Main Pressure :		9.43	kN	Min :	8.96	kN	Punch NO.;	44
	SD :	3.00	%	Max :	10.36	kN	Punch NO.;	17
Filling Depth :	Increase ;	2653	Times	Decrease ;	2658	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.00	mm	Pre Thickness ;	5.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.93	mm	Main Thickness ;	2.93	mm
Filling Depth :	7.25	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.760	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	2
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	46
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	747100	Tablets			
A.W.C Counter :	744139	Tablets			
HEP :	621 (0.1%)	Tablets	LEP :	238 (0.0%)	Tablets
GOOD :	743280 (99.9%)	Tablets			