

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 200MG,STVI1A00
User ID :	yu98249	Batch NO. :	VIM2500620
Print Interval :	50000 Tablets	Running Time :	06 Hour 09 Min 33 Sec
Total Counter :	900372	Total Running Time :	3090 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1740000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	11.20	kN	No		
HEP :	20.0 %	10.93	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.24	kN	Yes 15	Times	
Ref :		9.10	kN			
LCP :	1.5 %	8.97	kN	Yes 15	Times	
LEP :	20.0 %	7.28	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.01	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.35	kN	Min :	2.33	kN	Punch NO.;	17
SD :	0.50	%	Max :	2.39	kN	Punch NO.;	6
Mean Main Pressure :	9.11	kN	Min :	8.54	kN	Punch NO.;	12
SD :	3.00	%	Max :	9.98	kN	Punch NO.;	6
Filling Depth :	Increase ; 20	Times	Decrease ;	38	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.27	mm
Filling Depth :	5.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.751	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.22	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	7
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	900372	Tablets			
A.W.C Counter :	891900	Tablets			
HEP :	98 (0.0%)	Tablets	LEP :	40 (0.0%)	Tablets
GOOD :	891762 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICL 200MG,STVI1A00
User ID :	yu98249	Batch NO. :	VIM2500620
Print Interval :	50000 Tablets	Running Time :	06 Hour 09 Min 33 Sec
Total Counter :	900372	Total Running Time :	3090 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1740000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	11.40	kN	No		
HEP :	20.0 %	11.12	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.41	kN	Yes 15	Times	
Ref :		9.27	kN			
LCP :	1.5 %	9.13	kN	Yes 15	Times	
LEP :	20.0 %	7.42	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.14	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.50	kN	Min :	2.46	kN	Punch NO.;	47
SD :	0.70	%	Max :	2.54	kN	Punch NO.;	7
Mean Main Pressure :	9.34	kN	Min :	8.74	kN	Punch NO.;	9
SD :	3.10	%	Max :	10.15	kN	Punch NO.;	6
Filling Depth :	Increase ; 47	Times	Decrease ;	51	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.10	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.50	mm
Filling Depth :	5.77	mm	Current Cam :	Cam B	
Main Air pressure :	0.751	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.22	kN	Max Punch ;	62
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	7
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	900372	Tablets			
A.W.C Counter :	891900	Tablets			
HEP :	98 (0.0%)	Tablets	LEP :	40 (0.0%)	Tablets
GOOD :	891762 (100.0%)	Tablets			