

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo300mg STUB2B00
User ID :	sj97904	Batch NO. :	UBM2502030
Print Interval :	50000 Tablets	Running Time :	05 Hour 06 Min 44 Sec
Total Counter :	650232	Total Running Time :	3117 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	47	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	13.43	kN	No		
HEP :	20.0 %	13.10	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	11.08	kN	Yes 15	Times	
Ref :		10.91	kN			
LCP :	1.5 %	10.75	kN	Yes 15	Times	
LEP :	20.0 %	8.73	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	8.40	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.22	kN	Min :	1.17	kN	Punch NO.;	32
		2.90	%	Max :	1.31	kN	Punch NO.;	15
Mean Main Pressure :		10.77	kN	Min :	10.00	kN	Punch NO.;	8
	SD :	3.60	%	Max :	11.77	kN	Punch NO.;	52
Filling Depth :	Increase ;	1195	Times	Decrease ;	1206	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.27	mm	Main Thickness ;	3.27	mm
Filling Depth :	6.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650232	Tablets			
A.W.C Counter :	647036	Tablets			
HEP :	61 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	646975 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Allo300mg STUB2B00
User ID :	sj97904	Batch NO. :	UBM2502030
Print Interval :	50000 Tablets	Running Time :	05 Hour 06 Min 44 Sec
Total Counter :	650232	Total Running Time :	3117 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	23.0 %	12.00	kN	No		
HEP :	20.0 %	11.70	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.90	kN	Yes 15	Times	
Ref :		9.75	kN			
LCP :	1.5 %	9.61	kN	Yes 15	Times	
LEP :	20.0 %	7.80	kN	Yes 10	Rotations 15	Tablets
LSP :	23.0 %	7.51	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	0.67	kN	Min :	0.62	kN	Punch NO.;	41
		3.10	%	Max :	0.71	kN	Punch NO.;	11
Mean Main Pressure :	SD :	9.77	kN	Min :	8.97	kN	Punch NO.;	42
		4.60	%	Max :	10.95	kN	Punch NO.;	27
Filling Depth :	Increase ;	948	Times	Decrease ;	926	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.37	mm	Main Thickness ;	3.37	mm
Filling Depth :	6.88	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	51
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650232	Tablets			
A.W.C Counter :	647089	Tablets			
HEP :	61 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	647028 (100.0%)	Tablets			