

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	pr190041	Batch NO. :	HAM2501075
Print Interval :	50000 Tablets	Running Time :	04 Hour 11 Min 51 Sec
Total Counter :	398672	Total Running Time :	3129 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	199	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.78	kN	No		
HEP :	25.0 %	11.33	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.20	kN	Yes 15	Times	
Ref :		9.07	kN			
LCP :	1.5 %	8.93	kN	Yes 15	Times	
LEP :	25.0 %	6.80	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.59	kN	Min :	1.49	kN	Punch NO.;	42
SD :	2.80	%	Max :	1.72	kN	Punch NO.;	4
Mean Main Pressure :	9.05	kN	Min :	8.46	kN	Punch NO.;	42
SD :	2.40	%	Max :	9.45	kN	Punch NO.;	19
Filling Depth :	Increase ; 21	Times	Decrease ; 45	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.99	mm	Main Thickness ;	4.00	mm
Filling Depth :	9.58	mm	Current Cam :	Cam C	
Main Air pressure :	0.820	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.30	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	398672	Tablets			
A.W.C Counter :	395274	Tablets			
HEP :	0 (0%)	Tablets	LEP :	11 (0.0%)	Tablets
GOOD :	395263 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	pr190041	Batch NO. :	HAM2501075
Print Interval :	50000 Tablets	Running Time :	04 Hour 11 Min 51 Sec
Total Counter :	398672	Total Running Time :	3129 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	184	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.28	kN	No		
HEP :	25.0 %	10.84	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	8.80	kN	Yes 15	Times	
Ref :		8.67	kN			
LCP :	1.5 %	8.54	kN	Yes 15	Times	
LEP :	25.0 %	6.50	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.07	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.31	kN	Min :	1.22	kN	Punch NO.;	24
SD :	3.20	%	Max :	1.40	kN	Punch NO.;	39
Mean Main Pressure :	8.67	kN	Min :	7.99	kN	Punch NO.;	7
SD :	3.10	%	Max :	9.12	kN	Punch NO.;	20
Filling Depth :	Increase ;	12	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.04	mm	Pre Thickness ;	5.05	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.18	mm	Main Thickness ;	4.19	mm
Filling Depth :	9.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.820	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.30	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.17	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	398672	Tablets			
A.W.C Counter :	395274	Tablets			
HEP :	0 (0%)	Tablets	LEP :	11 (0.0%)	Tablets
GOOD :	395263 (100.0%)	Tablets			