

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	rp98927	Batch NO. :	HAM2501175
Print Interval :	50000 Tablets	Running Time :	03 Hour 27 Min 28 Sec
Total Counter :	350106	Total Running Time :	3133 Hour 38 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	219	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	12.17	kN	No		
HEP :	25.0 %	11.70	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.50	kN	Yes 15	Times	
Ref :		9.36	kN			
LCP :	1.5 %	9.22	kN	Yes 15	Times	
LEP :	25.0 %	7.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.55	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.48	kN	Min :	1.36	kN	Punch NO.;	7
SD :	4.60	%	Max :	1.65	kN	Punch NO.;	51
Mean Main Pressure :	9.04	kN	Min :	8.26	kN	Punch NO.;	7
SD :	4.30	%	Max :	9.87	kN	Punch NO.;	51
Filling Depth :	Increase ; 466	Times	Decrease ;	471	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	35	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	6.99	mm	Main Thickness ;	4.00	mm
Filling Depth :	9.78	mm	Current Cam :	Cam C	
Main Air pressure :	0.743	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.30	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350106	Tablets			
A.W.C Counter :	345986	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	79 (0.0%)	Tablets
GOOD :	345898 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	rp98927	Batch NO. :	HAM2501175
Print Interval :	50000 Tablets	Running Time :	03 Hour 27 Min 28 Sec
Total Counter :	350106	Total Running Time :	3133 Hour 38 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	219	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.98	kN	No		
HEP :	25.0 %	11.52	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	9.35	kN	Yes 15	Times	
Ref :		9.22	kN			
LCP :	1.5 %	9.08	kN	Yes 15	Times	
LEP :	25.0 %	6.91	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.45	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.23	kN	Min :	1.12	kN	Punch NO.;	13
SD :	5.30	%	Max :	1.39	kN	Punch NO.;	22
Mean Main Pressure :	8.93	kN	Min :	8.35	kN	Punch NO.;	52
SD :	4.10	%	Max :	9.71	kN	Punch NO.;	2
Filling Depth :	Increase ;	527	Times	Decrease ;	523	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	35	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.04	mm	Pre Thickness ;	5.05	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.18	mm	Main Thickness ;	4.19	mm
Filling Depth :	10.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.743	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.30	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350106	Tablets			
A.W.C Counter :	345986	Tablets			
HEP :	9 (0.0%)	Tablets	LEP :	79 (0.0%)	Tablets
GOOD :	345898 (100.0%)	Tablets			