

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	rk99163	Batch NO. :	HAM2501275
Print Interval :	50000 Tablets	Running Time :	02 Hour 58 Min 17 Sec
Total Counter :	301180	Total Running Time :	3138 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	219	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	11.47	kN	No		
HEP :	25.0 %	11.02	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	8.95	kN	Yes 15	Times	
Ref :		8.82	kN			
LCP :	1.5 %	8.69	kN	Yes 15	Times	
LEP :	25.0 %	6.61	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.17	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.52	kN	Min :	1.39	kN	Punch NO.;	42
SD :	2.70	%	Max :	1.62	kN	Punch NO.;	3
Mean Main Pressure :	8.75	kN	Min :	7.96	kN	Punch NO.;	42
SD :	2.90	%	Max :	9.23	kN	Punch NO.;	3
Filling Depth :	Increase ;	733	Times	Decrease ;	728	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	35	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.19	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.00	mm	Main Thickness ;	4.01	mm
Filling Depth :	9.38	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.776	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.29	kN	Max Punch ;	5
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	301180	Tablets			
A.W.C Counter :	295039	Tablets			
HEP :	127 (0.0%)	Tablets	LEP :	43 (0.0%)	Tablets
GOOD :	294869 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METHO 750MG,STHA1B00
User ID :	rk99163	Batch NO. :	HAM2501275
Print Interval :	50000 Tablets	Running Time :	02 Hour 58 Min 17 Sec
Total Counter :	301180	Total Running Time :	3138 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	219	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	10.87	kN	No		
HEP :	25.0 %	10.45	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	8.48	kN	Yes 15	Times	
Ref :		8.36	kN			
LCP :	1.5 %	8.23	kN	Yes 15	Times	
LEP :	25.0 %	6.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.85	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.20	kN	Min :	1.12	kN	Punch NO.;	37
SD :	3.20	%	Max :	1.30	kN	Punch NO.;	20
Mean Main Pressure :	8.33	kN	Min :	7.90	kN	Punch NO.;	10
SD :	2.60	%	Max :	9.02	kN	Punch NO.;	20
Filling Depth :	Increase ;	799	Times	Decrease ;	814	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	35	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.04	mm	Pre Thickness ;	5.05	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	7.19	mm	Main Thickness ;	4.20	mm
Filling Depth :	9.35	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.776	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.28	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	301180	Tablets			
A.W.C Counter :	295039	Tablets			
HEP :	127 (0.0%)	Tablets	LEP :	43 (0.0%)	Tablets
GOOD :	294869 (99.9%)	Tablets			