

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	yu98249	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	21 Hour 38 Min 44 Sec
Total Counter :	5554556	Total Running Time :	3161 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.96	kN	No		
HEP :	25.0 %	17.27	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	14.02	kN	Yes 15	Times	
Ref :		13.82	kN			
LCP :	1.5 %	13.61	kN	Yes 15	Times	
LEP :	25.0 %	10.36	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.67	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.56	kN	Min :	1.52	kN	Punch NO.;	42
SD :	0.80	%	Max :	1.59	kN	Punch NO.;	34
Mean Main Pressure :	13.94	kN	Min :	12.17	kN	Punch NO.;	6
SD :	3.80	%	Max :	15.12	kN	Punch NO.;	71
Filling Depth :	Increase ; 86	Times	Decrease ;	165	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	5.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	4
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5554556	Tablets			
A.W.C Counter :	5548448	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	5548448 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	yu98249	Batch NO. :	SHM2503850
Print Interval :	50000 Tablets	Running Time :	21 Hour 38 Min 45 Sec
Total Counter :	5554622	Total Running Time :	3161 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.64	kN	No		
HEP :	25.0 %	17.92	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	14.55	kN	Yes 15	Times	
Ref :		14.34	kN			
LCP :	1.5 %	14.12	kN	Yes 15	Times	
LEP :	25.0 %	10.75	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.04	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.44	kN	Punch NO.;	74
SD :	1.10	%	Max :	1.52	kN	Punch NO.;	29
Mean Main Pressure :	14.32	kN	Min :	13.15	kN	Punch NO.;	5
SD :	4.00	%	Max :	15.90	kN	Punch NO.;	68
Filling Depth :	Increase ;	47	Times	Decrease ;	84	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.15	mm	Main Thickness ;	2.16	mm
Filling Depth :	5.61	mm	Current Cam :	Cam B	
Main Air pressure :	0.757	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.27	kN	Max Punch ;	4
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	5554622	Tablets			
A.W.C Counter :	5548448	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	5548448 (100.0%)	Tablets			