

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	yu98249	Batch NO. :	SHM2503950
Print Interval :	50000 Tablets	Running Time :	18 Hour 42 Min 12 Sec
Total Counter :	4854230	Total Running Time :	3181 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.34	kN	No		
HEP :	25.0 %	17.63	kN	Yes 10	Rotations 15	Tablets
HCP :	1.5 %	14.32	kN	Yes 15	Times	
Ref :		14.11	kN			
LCP :	1.5 %	13.89	kN	Yes 15	Times	
LEP :	25.0 %	10.58	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.87	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.57	kN	Min :	1.55	kN	Punch NO.;	74
SD :	0.70	%	Max :	1.61	kN	Punch NO.;	41
Mean Main Pressure :	14.23	kN	Min :	12.94	kN	Punch NO.;	7
SD :	3.90	%	Max :	16.27	kN	Punch NO.;	39
Filling Depth :	Increase ;	161	Times	Decrease ;	222	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.06	mm	Main Thickness ;	2.07	mm
Filling Depth :	5.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.783	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.31	kN	Max Punch ;	35
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4854230	Tablets			
A.W.C Counter :	4848920	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	4848920 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50mg STSH4A00
User ID :	yu98249	Batch NO. :	SHM2503950
Print Interval :	50000 Tablets	Running Time :	18 Hour 42 Min 12 Sec
Total Counter :	4854230	Total Running Time :	3181 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.77	kN	No		
HEP :	25.0 %	18.05	kN	Yes	10	Rotations 15 Tablets
HCP :	1.5 %	14.66	kN	Yes	15	Times
Ref :		14.44	kN			
LCP :	1.5 %	14.22	kN	Yes	15	Times
LEP :	25.0 %	10.83	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.11	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.45	kN	Punch NO.;	17
SD :	0.90	%	Max :	1.52	kN	Punch NO.;	21
Mean Main Pressure :	14.42	kN	Min :	12.32	kN	Punch NO.;	74
SD :	5.20	%	Max :	16.30	kN	Punch NO.;	60
Filling Depth :	Increase ;	77	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.16	mm	Main Thickness ;	2.17	mm
Filling Depth :	5.56	mm	Current Cam :	Cam B	
Main Air pressure :	0.783	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.29	kN	Max Punch ;	2
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	23
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4854230	Tablets			
A.W.C Counter :	4848920	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	4848920 (100.0%)	Tablets			