

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIU1B00
User ID :	am98755	Batch NO. :	IUM2501240
Print Interval :	50000 Tablets	Running Time :	00 Hour 54 Min 25 Sec
Total Counter :	100036	Total Running Time :	3192 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.95	kN	No		
HEP :	24.0 %	27.61	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	22.71	kN	Yes 20	Times	
Ref :		22.27	kN			
LCP :	2.0 %	21.82	kN	Yes 20	Times	
LEP :	24.0 %	16.92	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	15.59	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.58	kN	Min :	2.49	kN	Punch NO.;	7
		1.90	%	Max :	2.71	kN	Punch NO.;	12
Mean Main Pressure :		21.99	kN	Min :	20.23	kN	Punch NO.;	8
	SD :	5.10	%	Max :	25.91	kN	Punch NO.;	25
Filling Depth :	Increase ;	22	Times	Decrease ;	10	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	7.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.15	kN	Max Punch ;	38
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.36	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100036	Tablets			
A.W.C Counter :	95308	Tablets			
HEP :	38 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	95269 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIU1B00
User ID :	am98755	Batch NO. :	IUM2501240
Print Interval :	50000 Tablets	Running Time :	00 Hour 54 Min 25 Sec
Total Counter :	100036	Total Running Time :	3192 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.04	kN	No		
HEP :	24.0 %	25.79	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.22	kN	Yes 20	Times	
Ref :		20.80	kN			
LCP :	2.0 %	20.38	kN	Yes 20	Times	
LEP :	24.0 %	15.81	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.49	kN	Min :	2.37	kN	Punch NO.;	51
SD :	2.60	%	Max :	2.67	kN	Punch NO.;	25
Mean Main Pressure :	20.86	kN	Min :	19.06	kN	Punch NO.;	7
SD :	5.10	%	Max :	23.85	kN	Punch NO.;	25
Filling Depth :	Increase ; 26	Times	Decrease ;	20	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.70	mm	Pre Thickness ;	2.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.29	mm	Main Thickness ;	2.30	mm
Filling Depth :	6.86	mm	Current Cam :	Cam C	
Main Air pressure :	0.762	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.15	kN	Max Punch ;	38
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.36	kN	Max Punch ;	11
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100036	Tablets			
A.W.C Counter :	95308	Tablets			
HEP :	38 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	95269 (100.0%)	Tablets			