

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 400 MG,STIU1B00
User ID :	yu98249	Batch NO. :	IUM2501240
Print Interval :	50000 Tablets	Running Time :	13 Hour 36 Min 05 Sec
Total Counter :	1550538	Total Running Time :	3204 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	180	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.1	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.18	kN	No		
HEP :	24.0 %	24.97	kN	Yes 10	Rotations 20	Tablets
HCP :	2.0 %	20.54	kN	Yes 20	Times	
Ref :		20.14	kN			
LCP :	2.0 %	19.73	kN	Yes 20	Times	
LEP :	24.0 %	15.30	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.10	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.59	kN	Min :	2.45	kN	Punch NO.;	12
SD :	2.60	%	Max :	2.78	kN	Punch NO.;	25
Mean Main Pressure :	20.39	kN	Min :	18.68	kN	Punch NO.;	10
SD :	4.80	%	Max :	23.54	kN	Punch NO.;	25
Filling Depth :	Increase ; 234	Times	Decrease ;	210	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.75	mm	Pre Thickness ;	2.76	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.44	mm	Current Cam :	Cam C	
Main Air pressure :	0.815	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	37
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1550538	Tablets			
A.W.C Counter :	1544974	Tablets			
HEP :	1305 (0.1%)	Tablets	LEP :	64 (0.0%)	Tablets
GOOD :	1543605 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : yu98249 Print Interval : 50000 Tablets Total Counter : 1550538 Station : Station 2	Product Name : IBU 400 MG,STIU1B00 Batch NO. : IUM2501240 Running Time : 13 Hour 36 Min 05 Sec Total Running Time : 3204 Hour 56 Min
---	---

Setting Value

Feeder :	Auto ;	180	%	Manual ;	21	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.1	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.16	kN	No		
HEP :	24.0 %	22.09	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	18.17	kN	Yes 20	Times	
Ref :		17.81	kN			
LCP :	2.0 %	17.46	kN	Yes 20	Times	
LEP :	24.0 %	13.54	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	12.47	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.43	kN	Min :	2.30	kN	Punch NO.;	51
		2.50	%	Max :	2.65	kN	Punch NO.;	25
Mean Main Pressure :		18.24	kN	Min :	16.75	kN	Punch NO.;	52
	SD :	4.20	%	Max :	21.22	kN	Punch NO.;	25
Filling Depth :	Increase ;	186	Times	Decrease ;	167	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	32	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	2.81	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	2.46	mm
Filling Depth :	7.02	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.815	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	37
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	44
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1550538	Tablets			
A.W.C Counter :	1544974	Tablets			
HEP :	1305 (0.1%)	Tablets	LEP :	64 (0.0%)	Tablets
GOOD :	1543605 (99.9%)	Tablets			