

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba 600mg STKS1A00
User ID :	cj99902	Batch NO. :	KSM2500160
Print Interval :	50000 Tablets	Running Time :	17 Hour 30 Min 38 Sec
Total Counter :	1997448	Total Running Time :	3208 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	23	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.96	kN	No		
HEP :	25.0 %	18.23	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.88	kN	Yes 15	Times	
Ref :		14.59	kN			
LCP :	2.0 %	14.30	kN	Yes 15	Times	
LEP :	25.0 %	10.94	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.21	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.30	kN	Min :	2.18	kN	Punch NO.;	22
SD :	3.10	%	Max :	2.51	kN	Punch NO.;	12
Mean Main Pressure :	14.38	kN	Min :	12.19	kN	Punch NO.;	46
SD :	7.70	%	Max :	17.05	kN	Punch NO.;	25
Filling Depth :	Increase ; 438	Times	Decrease ;	332	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.30	mm	Main Thickness ;	4.30	mm
Filling Depth :	7.80	mm	Current Cam :	Cam B	
Main Air pressure :	0.823	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	57	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.12	kN	Max Punch ;	36
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	45
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1997448	Tablets			
A.W.C Counter :	1989178	Tablets			
HEP :	1453 (0.1%)	Tablets	LEP :	310 (0.0%)	Tablets
GOOD :	1987415 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Gaba 600mg STKS1A00
User ID :	cj99902	Batch NO. :	KSM2500160
Print Interval :	50000 Tablets	Running Time :	17 Hour 30 Min 38 Sec
Total Counter :	1997448	Total Running Time :	3208 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	120	%	Manual ;	27	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.57	kN	No		
HEP :	25.0 %	16.89	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.79	kN	Yes 15	Times	
Ref :		13.52	kN			
LCP :	2.0 %	13.25	kN	Yes 15	Times	
LEP :	25.0 %	10.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.46	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.25	kN	Min :	2.15	kN	Punch NO.;	5
SD :	2.40	%	Max :	2.39	kN	Punch NO.;	3
Mean Main Pressure :	14.46	kN	Min :	13.42	kN	Punch NO.;	52
SD :	4.40	%	Max :	16.28	kN	Punch NO.;	3
Filling Depth :	Increase ;	256	Times	Decrease ;	210	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.20	mm	Pre Thickness ;	5.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.58	mm	Main Thickness ;	4.58	mm
Filling Depth :	7.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.823	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	57	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.11	kN	Max Punch ;	36
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	45
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1997448	Tablets			
A.W.C Counter :	1989178	Tablets			
HEP :	1453 (0.1%)	Tablets	LEP :	310 (0.0%)	Tablets
GOOD :	1987415 (99.9%)	Tablets			