

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	rp98927	Batch NO. :	EGM2500110
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 59 Sec
Total Counter :	450212	Total Running Time :	3212 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.19	kN	No		
HEP :	20.0 %	8.82	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.50	kN	Yes 15	Times	
Ref :		7.35	kN			
LCP :	2.0 %	7.21	kN	Yes 15	Times	
LEP :	20.0 %	5.88	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.52	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.65	kN	Min :	1.63	kN	Punch NO.;	8
SD :	0.60	%	Max :	1.68	kN	Punch NO.;	6
Mean Main Pressure :	7.33	kN	Min :	6.93	kN	Punch NO.;	8
SD :	2.40	%	Max :	7.67	kN	Punch NO.;	25
Filling Depth :	Increase ; 16	Times	Decrease ; 18	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.59	mm	Main Thickness ;	2.59	mm
Filling Depth :	4.50	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	54	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	56
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450212	Tablets			
A.W.C Counter :	432646	Tablets			
HEP :	20 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	432589 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	rp98927	Batch NO. :	EGM2500110
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 59 Sec
Total Counter :	450212	Total Running Time :	3212 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	47	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.36	kN	No		
HEP :	20.0 %	8.99	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.64	kN	Yes 15	Times	
Ref :		7.49	kN			
LCP :	2.0 %	7.34	kN	Yes 15	Times	
LEP :	20.0 %	5.99	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.62	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.58	kN	Min :	1.55	kN	Punch NO.;	8
SD :	0.70	%	Max :	1.62	kN	Punch NO.;	14
Mean Main Pressure :	7.43	kN	Min :	6.93	kN	Punch NO.;	8
SD :	3.40	%	Max :	8.04	kN	Punch NO.;	59
Filling Depth :	Increase ;	32	Times	Decrease ;	35	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	4.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.756	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	54	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	56
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	450212	Tablets			
A.W.C Counter :	432646	Tablets			
HEP :	20 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	432589 (100.0%)	Tablets			