

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	pb97604	Batch NO. :	EGM2500210
Print Interval :	50000 Tablets	Running Time :	01 Hour 06 Min 54 Sec
Total Counter :	150048	Total Running Time :	3217 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.60	kN	No		
HEP :	20.0 %	9.21	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	7.83	kN	Yes	15	Times
Ref :		7.68	kN			
LCP :	2.0 %	7.52	kN	Yes	15	Times
LEP :	20.0 %	6.14	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	5.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.58	kN	Min :	1.56	kN	Punch NO.;	29
SD :	0.50	%	Max :	1.60	kN	Punch NO.;	16
Mean Main Pressure :	7.74	kN	Min :	7.32	kN	Punch NO.;	31
SD :	2.90	%	Max :	8.38	kN	Punch NO.;	25
Filling Depth :	Increase ;	30	Times	Decrease ;	26	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	2.59	mm
Filling Depth :	5.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.775	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	60	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	62
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.25	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150048	Tablets			
A.W.C Counter :	139664	Tablets			
HEP :	72 (0.1%)	Tablets	LEP :	77 (0.1%)	Tablets
GOOD :	139515 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	pb97604	Batch NO. :	EGM2500210
Print Interval :	50000 Tablets	Running Time :	01 Hour 06 Min 54 Sec
Total Counter :	150048	Total Running Time :	3217 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.79	kN	No		
HEP :	20.0 %	8.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.17	kN	Yes 15	Times	
Ref :		7.03	kN			
LCP :	2.0 %	6.89	kN	Yes 15	Times	
LEP :	20.0 %	5.62	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.45	kN	Punch NO.;	6
SD :	0.60	%	Max :	1.51	kN	Punch NO.;	40
Mean Main Pressure :	7.07	kN	Min :	6.62	kN	Punch NO.;	63
SD :	3.20	%	Max :	8.01	kN	Punch NO.;	25
Filling Depth :	Increase ;	32	Times	Decrease ;	37	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	4.50	mm	Current Cam :	Cam B	
Main Air pressure :	0.775	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	60	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	60
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.25	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150048	Tablets			
A.W.C Counter :	139664	Tablets			
HEP :	72 (0.1%)	Tablets	LEP :	77 (0.1%)	Tablets
GOOD :	139515 (99.9%)	Tablets			