

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	pb97604	Batch NO. :	EGM2500210
Print Interval :	50000 Tablets	Running Time :	01 Hour 28 Min 10 Sec
Total Counter :	200050	Total Running Time :	3217 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	23	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.60	kN	No		
HEP :	20.0 %	9.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.83	kN	Yes 15	Times	
Ref :		7.68	kN			
LCP :	2.0 %	7.52	kN	Yes 15	Times	
LEP :	20.0 %	6.14	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.76	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.57	kN	Min :	1.55	kN	Punch NO.;	6
SD :	0.50	%	Max :	1.59	kN	Punch NO.;	55
Mean Main Pressure :	7.66	kN	Min :	7.08	kN	Punch NO.;	13
SD :	2.60	%	Max :	8.13	kN	Punch NO.;	25
Filling Depth :	Increase ; 31	Times	Decrease ; 28	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	2.59	mm
Filling Depth :	4.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.757	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	62
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.28	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200050	Tablets			
A.W.C Counter :	189498	Tablets			
HEP :	72 (0.0%)	Tablets	LEP :	199 (0.1%)	Tablets
GOOD :	189227 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	pb97604	Batch NO. :	EGM2500210
Print Interval :	50000 Tablets	Running Time :	01 Hour 28 Min 10 Sec
Total Counter :	200050	Total Running Time :	3217 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	53	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.79	kN	No		
HEP :	20.0 %	8.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.17	kN	Yes 15	Times	
Ref :		7.03	kN			
LCP :	2.0 %	6.89	kN	Yes 15	Times	
LEP :	20.0 %	5.62	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.48	kN	Min :	1.43	kN	Punch NO.;	6
SD :	0.70	%	Max :	1.49	kN	Punch NO.;	16
Mean Main Pressure :	6.93	kN	Min :	6.20	kN	Punch NO.;	13
SD :	3.10	%	Max :	7.52	kN	Punch NO.;	25
Filling Depth :	Increase ;	33	Times	Decrease ;	39	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	4.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.757	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	33	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	62
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.29	kN	Max Punch ;	5
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	200050	Tablets			
A.W.C Counter :	189498	Tablets			
HEP :	72 (0.0%)	Tablets	LEP :	199 (0.1%)	Tablets
GOOD :	189227 (99.9%)	Tablets			