

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | ENALA 10MG<br>STEG3B00 |
| User ID :        | rp98927       | Batch NO. :          | EGM2500210             |
| Print Interval : | 50000 Tablets | Running Time :       | 06 Hour 31 Min 26 Sec  |
| Total Counter :  | 864880        | Total Running Time : | 3222 Hour 40 Min       |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |       |                      |
|------------------------------------|--------|-------------------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 41                | %       | Manual ;           | 10    | RPM                  |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min : | 2.50 mm              |
| Target Quantity :                  |        | 1000000           | Tablets |                    | Max : | 8.00 mm              |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |                   |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 50                | Min     | Supply Time ;      | 0.2   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 60                | Min     | Supply Time ;      | 1.0   | Sec                  |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 2                 | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |       |                      |
|                                    |        |                   |         | Stop Condition ;   |       |                      |
| HSP :                              | 25.0 % | 9.60              | kN      | No                 |       |                      |
| HEP :                              | 20.0 % | 9.21              | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 2.0 %  | 7.83              | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 7.68              | kN      |                    |       |                      |
| LCP :                              | 2.0 %  | 7.52              | kN      | Yes                | 15    | Times                |
| LEP :                              | 20.0 % | 6.14              | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 25.0 % | 5.76              | kN      | No                 |       |                      |
| SD limit :                         | 45.0 % |                   |         | Yes                |       |                      |
| Pre HSP                            |        | 40.00             | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2     | Rotations            |
| Empty Punch No. :                  | None   |                   |         |                    |       |                      |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.52       | kN | Min : | 1.49       | kN | Punch NO.; | 21 |
| SD :                 | 0.50       | %  | Max : | 1.54       | kN | Punch NO.; | 50 |
| Mean Main Pressure : | 7.52       | kN | Min : | 7.00       | kN | Punch NO.; | 47 |
| SD :                 | 2.50       | %  | Max : | 7.87       | kN | Punch NO.; | 37 |
| Filling Depth :      | Increase ; | 34 | Times | Decrease ; | 36 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 16      | RPM | Capacity :       | 124800   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 7        | RPM          |
| Pre Upper Punch Position ;    | 2.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.20    | mm  | Pre Thickness ;  | 3.20     | mm           |
| Main Upper Punch Position ;   | 2.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.59    | mm  | Main Thickness ; | 2.59     | mm           |
| Filling Depth :               | 4.46    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.769   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 10      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 16      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.14 | kN | Max Punch ; | 38 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.31 | kN | Max Punch ; | 20 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 864880            | Tablets |       |            |         |
| A.W.C Counter : | 851650            | Tablets |       |            |         |
| HEP :           | 165 (0.0%)        | Tablets | LEP : | 965 (0.1%) | Tablets |
| GOOD :          | 850520<br>(99.9%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | ENALA 10MG<br>STEG3B00 |
| User ID :        | rp98927       | Batch NO. :          | EGM2500210             |
| Print Interval : | 50000 Tablets | Running Time :       | 06 Hour 31 Min 26 Sec  |
| Total Counter :  | 864880        | Total Running Time : | 3222 Hour 40 Min       |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 42                | %       | Manual ;           | 27           | RPM       |
| Filling Cam :                      |        | Cam B<br>4.5-10mm |         | Cam Range :        | Min :        | 2.50 mm   |
| Target Quantity :                  |        | 1000000           | Tablets |                    | Max :        | 8.00 mm   |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 50                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 60                | Min     | Supply Time ;      | 1.0          | Sec       |
| Powder Supply Time :               |        | 60.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 2                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 2.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 3.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.90              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 25.0 % | 8.79              | kN      | No                 |              |           |
| HEP :                              | 20.0 % | 8.44              | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 7.17              | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 7.03              | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 6.89              | kN      | Yes 15             | Times        |           |
| LEP :                              | 20.0 % | 5.62              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 25.0 % | 5.27              | kN      | No                 |              |           |
| SD limit :                         | 45.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 40.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |    |       |            |    |            |    |
|----------------------|------------|----|-------|------------|----|------------|----|
| Mean Pre Pressure :  | 1.44       | kN | Min : | 1.39       | kN | Punch NO.; | 21 |
| SD :                 | 0.60       | %  | Max : | 1.46       | kN | Punch NO.; | 34 |
| Mean Main Pressure : | 7.13       | kN | Min : | 6.64       | kN | Punch NO.; | 53 |
| SD :                 | 2.90       | %  | Max : | 7.61       | kN | Punch NO.; | 63 |
| Filling Depth :      | Increase ; | 27 | Times | Decrease ; | 28 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 16      | RPM | Capacity :       | 124800   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 7        | RPM          |
| Pre Upper Punch Position ;    | 2.00    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 5.20    | mm  | Pre Thickness ;  | 3.20     | mm           |
| Main Upper Punch Position ;   | 2.00    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 4.75    | mm  | Main Thickness ; | 2.75     | mm           |
| Filling Depth :               | 4.52    | mm  | Current Cam :    | Cam B    |              |
| Main Air pressure :           | 0.769   | MPa |                  | 4.5-10mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 10      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 16      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.11 | kN |             |    |
|                  | Max ;     | 0.14 | kN | Max Punch ; | 38 |
| Lower Punch :    | Average ; | 0.14 | kN |             |    |
|                  | Max ;     | 0.34 | kN | Max Punch ; | 20 |
| Ejection Force : | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 864880            | Tablets |       |            |         |
| A.W.C Counter : | 851650            | Tablets |       |            |         |
| HEP :           | 165 (0.0%)        | Tablets | LEP : | 965 (0.1%) | Tablets |
| GOOD :          | 850520<br>(99.9%) | Tablets |       |            |         |