

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	sj97904	Batch NO. :	EGM2500310
Print Interval :	50000 Tablets	Running Time :	02 Hour 04 Min 29 Sec
Total Counter :	284360	Total Running Time :	3225 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	9.58	kN	No		
HEP :	20.0 %	9.20	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	7.82	kN	Yes	15	Times
Ref :		7.66	kN			
LCP :	2.0 %	7.51	kN	Yes	15	Times
LEP :	20.0 %	6.13	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	5.75	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.53	kN	Min :	1.50	kN	Punch NO.;	4
SD :	0.80	%	Max :	1.56	kN	Punch NO.;	12
Mean Main Pressure :	7.62	kN	Min :	7.11	kN	Punch NO.;	60
SD :	2.50	%	Max :	8.06	kN	Punch NO.;	6
Filling Depth :	Increase ;	12	Times	Decrease ;	14	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.59	mm	Main Thickness ;	2.59	mm
Filling Depth :	4.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	62
Lower Punch :	Average ;	0.22	kN		
	Max ;	0.33	kN	Max Punch ;	56
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	284360	Tablets			
A.W.C Counter :	275192	Tablets			
HEP :	241 (0.1%)	Tablets	LEP :	525 (0.2%)	Tablets
GOOD :	274426 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ENALA 10MG STEG3B00
User ID :	sj97904	Batch NO. :	EGM2500310
Print Interval :	50000 Tablets	Running Time :	02 Hour 04 Min 29 Sec
Total Counter :	284360	Total Running Time :	3225 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	27	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	8.91	kN	No		
HEP :	20.0 %	8.56	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.27	kN	Yes 15	Times	
Ref :		7.13	kN			
LCP :	2.0 %	6.99	kN	Yes 15	Times	
LEP :	20.0 %	5.71	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	5.35	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.45	kN	Min :	1.39	kN	Punch NO.;	36
SD :	1.10	%	Max :	1.48	kN	Punch NO.;	65
Mean Main Pressure :	7.09	kN	Min :	6.75	kN	Punch NO.;	60
SD :	2.00	%	Max :	7.39	kN	Punch NO.;	61
Filling Depth :	Increase ;	13	Times	Decrease ;	17	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	3.20	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	2.75	mm
Filling Depth :	4.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.781	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	62
Lower Punch :	Average ;	0.22	kN		
	Max ;	0.32	kN	Max Punch ;	56
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	284360	Tablets			
A.W.C Counter :	275192	Tablets			
HEP :	241 (0.1%)	Tablets	LEP :	525 (0.2%)	Tablets
GOOD :	274426 (99.7%)	Tablets			