

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	pb97604	Batch NO. :	JBM2503640
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 37 Sec
Total Counter :	300104	Total Running Time :	3246 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	223	%	Manual ;	27	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	11.98	kN	No		
HEP :	20.0 %	11.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.77	kN	Yes 15	Times	
Ref :		9.58	kN			
LCP :	2.0 %	9.39	kN	Yes 15	Times	
LEP :	20.0 %	7.67	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	7.19	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.79	kN	Punch NO.;	33
SD :	1.10	%	Max :	1.89	kN	Punch NO.;	42
Mean Main Pressure :	9.63	kN	Min :	8.95	kN	Punch NO.;	34
SD :	2.70	%	Max :	10.28	kN	Punch NO.;	16
Filling Depth :	Increase ;	279	Times	Decrease ;	336	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	45	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.86	mm	Main Thickness ;	3.86	mm
Filling Depth :	12.69	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.745	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	46
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300104	Tablets			
A.W.C Counter :	291974	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	44 (0.0%)	Tablets
GOOD :	291915 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	pb97604	Batch NO. :	JBM2503640
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 37 Sec
Total Counter :	300104	Total Running Time :	3246 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	223	%	Manual ;	40	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	11.20	kN	No		
HEP :	20.0 %	10.75	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.14	kN	Yes	15	Times
Ref :		8.96	kN			
LCP :	2.0 %	8.78	kN	Yes	15	Times
LEP :	20.0 %	7.17	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	6.72	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.62	kN	Min :	1.57	kN	Punch NO.;	20
SD :	1.40	%	Max :	1.66	kN	Punch NO.;	12
Mean Main Pressure :	8.98	kN	Min :	8.53	kN	Punch NO.;	52
SD :	2.30	%	Max :	9.55	kN	Punch NO.;	16
Filling Depth :	Increase ;	290	Times	Decrease ;	290	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	45	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.05	mm	Main Thickness ;	4.05	mm
Filling Depth :	12.15	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.745	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	46
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	53
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	300104	Tablets			
A.W.C Counter :	291974	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	44 (0.0%)	Tablets
GOOD :	291915 (100.0%)	Tablets			