

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	rp98927	Batch NO. :	JBM2503640
Print Interval :	50000 Tablets	Running Time :	06 Hour 56 Min 55 Sec
Total Counter :	850352	Total Running Time :	3250 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	223	%	Manual ;	27	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	12.12	kN	No		
HEP :	20.0 %	11.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.89	kN	Yes	15	Times
Ref :		9.69	kN			
LCP :	2.0 %	9.50	kN	Yes	15	Times
LEP :	20.0 %	7.76	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	7.27	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.82	kN	Min :	1.78	kN	Punch NO.;	33
SD :	1.20	%	Max :	1.87	kN	Punch NO.;	12
Mean Main Pressure :	9.60	kN	Min :	9.01	kN	Punch NO.;	22
SD :	2.60	%	Max :	10.12	kN	Punch NO.;	4
Filling Depth :	Increase ;	318	Times	Decrease ;	390	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.86	mm	Main Thickness ;	3.86	mm
Filling Depth :	12.30	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.754	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	44
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	850352	Tablets			
A.W.C Counter :	841350	Tablets			
HEP :	60 (0.0%)	Tablets	LEP :	44 (0.0%)	Tablets
GOOD :	841246 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	rp98927	Batch NO. :	JBM2503640
Print Interval :	50000 Tablets	Running Time :	06 Hour 56 Min 55 Sec
Total Counter :	850352	Total Running Time :	3250 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	223	%	Manual ;	40	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	11.53	kN	No		
HEP :	20.0 %	11.07	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.41	kN	Yes 15	Times	
Ref :		9.22	kN			
LCP :	2.0 %	9.04	kN	Yes 15	Times	
LEP :	20.0 %	7.38	kN	Yes 10	Rotations 15	Tablets
LSP :	25.0 %	6.92	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.61	kN	Min :	1.57	kN	Punch NO.;	41
SD :	1.30	%	Max :	1.66	kN	Punch NO.;	27
Mean Main Pressure :	9.21	kN	Min :	8.52	kN	Punch NO.;	41
SD :	2.60	%	Max :	9.70	kN	Punch NO.;	28
Filling Depth :	Increase ;	306	Times	Decrease ;	310	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.05	mm	Main Thickness ;	4.05	mm
Filling Depth :	12.31	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.754	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.04	kN	Max Punch ;	44
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	850352	Tablets			
A.W.C Counter :	841350	Tablets			
HEP :	60 (0.0%)	Tablets	LEP :	44 (0.0%)	Tablets
GOOD :	841246 (100.0%)	Tablets			