

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	pb97604	Batch NO. :	JBM2503740
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 08 Sec
Total Counter :	350080	Total Running Time :	3259 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	225	%	Manual ;	27	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	12.05	kN	No		
HEP :	20.0 %	11.57	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.83	kN	Yes	15	Times
Ref :		9.64	kN			
LCP :	2.0 %	9.45	kN	Yes	15	Times
LEP :	20.0 %	7.71	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	7.23	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.75	kN	Min :	1.71	kN	Punch NO.;	46
SD :	1.30	%	Max :	1.81	kN	Punch NO.;	4
Mean Main Pressure :	9.57	kN	Min :	9.01	kN	Punch NO.;	34
SD :	2.70	%	Max :	10.24	kN	Punch NO.;	16
Filling Depth :	Increase ;	357	Times	Decrease ;	417	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	45	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.86	mm	Main Thickness ;	3.86	mm
Filling Depth :	13.09	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.749	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350080	Tablets			
A.W.C Counter :	343844	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	343838 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 40 MG,STJB1C00
User ID :	pb97604	Batch NO. :	JBM2503740
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 08 Sec
Total Counter :	350080	Total Running Time :	3259 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	225	%	Manual ;	40	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1500000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	25.0 %	11.44	kN	No		
HEP :	20.0 %	10.98	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.34	kN	Yes	15	Times
Ref :		9.15	kN			
LCP :	2.0 %	8.97	kN	Yes	15	Times
LEP :	20.0 %	7.32	kN	Yes	10	Rotations 15 Tablets
LSP :	25.0 %	6.86	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.64	kN	Min :	1.60	kN	Punch NO.;	33
SD :	1.20	%	Max :	1.71	kN	Punch NO.;	4
Mean Main Pressure :	9.10	kN	Min :	8.42	kN	Punch NO.;	27
SD :	2.20	%	Max :	9.62	kN	Punch NO.;	46
Filling Depth :	Increase ;	316	Times	Decrease ;	327	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	45	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.05	mm	Main Thickness ;	4.05	mm
Filling Depth :	12.56	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.749	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	15
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	47
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	350080	Tablets			
A.W.C Counter :	343844	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	343838 (100.0%)	Tablets			