

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	pb97604	Batch NO. :	JBM2502480
Print Interval :	50000 Tablets	Running Time :	05 Hour 49 Min 44 Sec
Total Counter :	601550	Total Running Time :	3274 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	337	%	Manual ;	27	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.68	kN	No		
HEP :	25.0 %	17.96	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.66	kN	Yes	15	Times
Ref :		14.37	kN			
LCP :	2.0 %	14.08	kN	Yes	15	Times
LEP :	25.0 %	10.78	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.06	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.74	kN	Min :	2.56	kN	Punch NO.;	34
SD :	3.10	%	Max :	2.93	kN	Punch NO.;	36
Mean Main Pressure :	14.02	kN	Min :	12.50	kN	Punch NO.;	37
SD :	4.30	%	Max :	15.41	kN	Punch NO.;	22
Filling Depth :	Increase ;	221	Times	Decrease ;	189	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	54	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.35	mm	Main Thickness ;	4.35	mm
Filling Depth :	15.77	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.763	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.16	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	601550	Tablets			
A.W.C Counter :	588301	Tablets			
HEP :	252 (0.0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	587851 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	pb97604	Batch NO. :	JBM2502480
Print Interval :	50000 Tablets	Running Time :	05 Hour 49 Min 44 Sec
Total Counter :	601550	Total Running Time :	3274 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	323	%	Manual ;	40	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.75	kN	No		
HEP :	25.0 %	17.06	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.92	kN	Yes	15	Times
Ref :		13.65	kN			
LCP :	2.0 %	13.38	kN	Yes	15	Times
LEP :	25.0 %	10.24	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.56	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.78	kN	Min :	2.65	kN	Punch NO.;	31
SD :	2.20	%	Max :	2.92	kN	Punch NO.;	29
Mean Main Pressure :	13.70	kN	Min :	12.76	kN	Punch NO.;	38
SD :	3.10	%	Max :	14.64	kN	Punch NO.;	48
Filling Depth :	Increase ;	102	Times	Decrease ;	122	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	52	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.99	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.50	mm	Main Thickness ;	4.50	mm
Filling Depth :	15.69	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.763	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.16	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	601550	Tablets			
A.W.C Counter :	588301	Tablets			
HEP :	252 (0.0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	587851 (99.9%)	Tablets			