

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	rp98927	Batch NO. :	JBM2502580
Print Interval :	50000 Tablets	Running Time :	05 Hour 18 Min 31 Sec
Total Counter :	550138	Total Running Time :	3281 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	345	%	Manual ;	160	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	18.29	kN	No		
HEP :	25.0 %	17.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.35	kN	Yes 15	Times	
Ref :		14.07	kN			
LCP :	2.0 %	13.79	kN	Yes 15	Times	
LEP :	25.0 %	10.55	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.85	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.81	kN	Min :	2.67	kN	Punch NO.;	21
SD :	3.20	%	Max :	3.00	kN	Punch NO.;	30
Mean Main Pressure :	13.94	kN	Min :	12.79	kN	Punch NO.;	21
SD :	4.50	%	Max :	15.41	kN	Punch NO.;	30
Filling Depth :	Increase ;	395	Times	Decrease ;	338	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	55	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	9.00	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.40	mm	Main Thickness ;	4.40	mm
Filling Depth :	16.27	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.742	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	1
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550138	Tablets			
A.W.C Counter :	540411	Tablets			
HEP :	426 (0.1%)	Tablets	LEP :	72 (0.0%)	Tablets
GOOD :	539913 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	rp98927	Batch NO. :	JBM2502580
Print Interval :	50000 Tablets	Running Time :	05 Hour 18 Min 31 Sec
Total Counter :	550138	Total Running Time :	3281 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	345	%	Manual ;	150	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		3.00	kN			
Ejecting Force High Limit :		4.90	kN			
				Stop Condition ;		
HSP :	30.0 %	17.17	kN	No		
HEP :	25.0 %	16.51	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.47	kN	Yes	15	Times
Ref :		13.20	kN			
LCP :	2.0 %	12.94	kN	Yes	15	Times
LEP :	25.0 %	9.90	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.24	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.73	kN	Min :	2.62	kN	Punch NO.;	33
SD :	2.30	%	Max :	2.87	kN	Punch NO.;	29
Mean Main Pressure :	13.12	kN	Min :	12.24	kN	Punch NO.;	23
SD :	3.00	%	Max :	13.86	kN	Punch NO.;	32
Filling Depth :	Increase ;	172	Times	Decrease ;	202	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	55	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.99	mm	Pre Thickness ;	6.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.55	mm	Main Thickness ;	4.55	mm
Filling Depth :	15.55	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.742	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	53
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	25
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550138	Tablets		
A.W.C Counter :	540411	Tablets		
HEP :	426 (0.1%)	Tablets	LEP :	72 (0.0%) Tablets
GOOD :	539913 (99.9%)	Tablets		