

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	rp98927	Batch NO. :	JBM2502680
Print Interval :	50000 Tablets	Running Time :	05 Hour 18 Min 17 Sec
Total Counter :	550186	Total Running Time :	3288 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	345	%	Manual ;	160	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.88	kN	No		
HEP :	25.0 %	16.23	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.25	kN	Yes	15	Times
Ref :		12.99	kN			
LCP :	2.0 %	12.73	kN	Yes	15	Times
LEP :	25.0 %	9.74	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.09	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.98	kN	Min :	2.81	kN	Punch NO.;	53
SD :	3.40	%	Max :	3.27	kN	Punch NO.;	3
Mean Main Pressure :	12.92	kN	Min :	11.79	kN	Punch NO.;	1
SD :	4.40	%	Max :	14.57	kN	Punch NO.;	3
Filling Depth :	Increase ;	533	Times	Decrease ;	522	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	55	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	8.80	mm	Pre Thickness ;	5.80	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.40	mm	Main Thickness ;	4.40	mm
Filling Depth :	16.11	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.688	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550186	Tablets			
A.W.C Counter :	541091	Tablets			
HEP :	82 (0.0%)	Tablets	LEP :	49 (0.0%)	Tablets
GOOD :	540960 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ATORV 80 MG,STJB1D00
User ID :	rp98927	Batch NO. :	JBM2502680
Print Interval :	50000 Tablets	Running Time :	05 Hour 18 Min 17 Sec
Total Counter :	550186	Total Running Time :	3288 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	345	%	Manual ;	150	RPM
Filling Cam :		Cam E 16.5- 22mm		Cam Range :	Min :	14.50 mm
Target Quantity :		750000	Tablets		Max :	20.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.97	kN	No		
HEP :	25.0 %	16.32	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.32	kN	Yes	15	Times
Ref :		13.05	kN			
LCP :	2.0 %	12.79	kN	Yes	15	Times
LEP :	25.0 %	9.79	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.14	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.00	kN	Min :	2.86	kN	Punch NO.;	39
SD :	2.40	%	Max :	3.14	kN	Punch NO.;	35
Mean Main Pressure :	13.22	kN	Min :	12.12	kN	Punch NO.;	38
SD :	3.40	%	Max :	14.23	kN	Punch NO.;	30
Filling Depth :	Increase ;	231	Times	Decrease ;	264	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	16	RPM	Capacity :	101760	Tablets/hour
Feeder : Status ;	Auto		Speed ;	55	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	8.80	mm	Pre Thickness ;	5.81	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	7.55	mm	Main Thickness ;	4.55	mm
Filling Depth :	15.52	mm	Current Cam :	Cam E 16.5- 22mm	
Main Air pressure :	0.688	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	1
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	4
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550186	Tablets			
A.W.C Counter :	541091	Tablets			
HEP :	82 (0.0%)	Tablets	LEP :	49 (0.0%)	Tablets
GOOD :	540960 (100.0%)	Tablets			