

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Atorva 10mg
User ID :	cj99902	Batch NO. :	ATV TAB XV 25 001
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 01 Sec
Total Counter :	100060	Total Running Time :	3291 Hour 14 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	160	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		210000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	8.22	kN	No		
HEP :	25.0 %	7.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	6.45	kN	Yes 15	Times	
Ref :		6.32	kN			
LCP :	2.0 %	6.19	kN	Yes 15	Times	
LEP :	25.0 %	4.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	4.42	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.30	kN	Min :	1.28	kN	Punch NO.;	14
		0.50	%	Max :	1.32	kN	Punch NO.;	71
Mean Main Pressure :		6.24	kN	Min :	5.54	kN	Punch NO.;	18
	SD :	5.40	%	Max :	6.99	kN	Punch NO.;	47
Filling Depth :	Increase ;	33	Times	Decrease ;	16	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	4.69	mm	Current Cam :	Cam B	
Main Air pressure :	0.741	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	30	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	41
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.24	kN	Max Punch ;	66
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100060	Tablets			
A.W.C Counter :	83901	Tablets			
HEP :	26 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	83875 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Atorva 10mg
User ID :	cj99902	Batch NO. :	ATV TAB XV 25 001
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 01 Sec
Total Counter :	100060	Total Running Time :	3291 Hour 14 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	60	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		210000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	8.52	kN	No		
HEP :	25.0 %	8.19	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	6.69	kN	Yes 15	Times	
Ref :		6.55	kN			
LCP :	2.0 %	6.42	kN	Yes 15	Times	
LEP :	25.0 %	4.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	4.59	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.32	kN	Min :	1.30	kN	Punch NO.;	16
SD :	0.70	%	Max :	1.34	kN	Punch NO.;	2
Mean Main Pressure :	6.56	kN	Min :	5.45	kN	Punch NO.;	28
SD :	6.60	%	Max :	7.83	kN	Punch NO.;	47
Filling Depth :	Increase ; 24	Times	Decrease ;	12	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	231000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.33	mm
Filling Depth :	5.04	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.741	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	30	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	41
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.24	kN	Max Punch ;	66
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	100060	Tablets			
A.W.C Counter :	83901	Tablets			
HEP :	26 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	83875 (100.0%)	Tablets			