

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	rp98927	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 05 Sec
Total Counter :	150012	Total Running Time :	3294 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	174	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.66	kN	No		
HEP :	25.0 %	9.29	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.58	kN	Yes 15	Times	
Ref :		7.43	kN			
LCP :	2.0 %	7.28	kN	Yes 15	Times	
LEP :	25.0 %	5.57	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.20	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.39	kN	Min :	1.18	kN	Punch NO.;	52
SD :	5.10	%	Max :	1.61	kN	Punch NO.;	49
Mean Main Pressure :	7.28	kN	Min :	6.46	kN	Punch NO.;	39
SD :	3.90	%	Max :	7.88	kN	Punch NO.;	24
Filling Depth :	Increase ; 122	Times	Decrease ;	105	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.55	mm	Main Thickness ;	3.55	mm
Filling Depth :	9.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.747	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	29
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.63	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150012	Tablets			
A.W.C Counter :	143652	Tablets			
HEP :	168 (0.1%)	Tablets	LEP :	36 (0.0%)	Tablets
GOOD :	143448 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GEMFI 600MG,STKF2A00
User ID :	rp98927	Batch NO. :	KFM2500260
Print Interval :	50000 Tablets	Running Time :	01 Hour 35 Min 05 Sec
Total Counter :	150012	Total Running Time :	3294 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	165	%	Manual ;	45	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		600000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		50	Min	Supply Time ;	0.6	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.02	kN	No		
HEP :	25.0 %	10.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.65	kN	Yes 15	Times	
Ref :		8.48	kN			
LCP :	2.0 %	8.31	kN	Yes 15	Times	
LEP :	25.0 %	6.36	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.93	kN	No		
SD limit :	45.0 %			Yes		
Pre HSP		40.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.86	kN	Punch NO.;	5
SD :	3.10	%	Max :	2.15	kN	Punch NO.;	46
Mean Main Pressure :	8.54	kN	Min :	8.13	kN	Punch NO.;	19
SD :	2.50	%	Max :	9.15	kN	Punch NO.;	17
Filling Depth :	Increase ; 36	Times	Decrease ; 57	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	3.90	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	6.60	mm	Main Thickness ;	3.60	mm
Filling Depth :	8.70	mm	Current Cam :	Cam C	
Main Air pressure :	0.747	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	29
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.62	kN	Max Punch ;	49
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	150012	Tablets			
A.W.C Counter :	143705	Tablets			
HEP :	168 (0.1%)	Tablets	LEP :	36 (0.0%)	Tablets
GOOD :	143501 (99.9%)	Tablets			