

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A0 0
User ID :	pb97604	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	09 Hour 59 Min 08 Sec
Total Counter :	1690220	Total Running Time :	333 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	76	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.42	kN	No		
HEP :	25.0 %	12.91	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.53	kN	Yes	10 Times	
Ref :		10.33	kN			
LCP :	2.0 %	10.12	kN	Yes	10 Times	
LEP :	25.0 %	7.74	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.64	kN	Min :	0.60	kN	Punch NO.;	58
SD :	1.80	%	Max :	0.67	kN	Punch NO.;	61
Mean Main Pressure :	10.21	kN	Min :	9.79	kN	Punch NO.;	17
SD :	2.10	%	Max :	10.66	kN	Punch NO.;	30
Filling Depth :	Increase ;	15	Times	Decrease ;	21	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.19	mm	Pre Thickness ;	4.69	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.73	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.811	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	18
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1690220	Tablets			
A.W.C Counter :	1669603	Tablets			
HEP :	513 (0.0%)	Tablets	LEP :	562 (0.0%)	Tablets
GOOD :	1668528 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MGSTVI1A0 0
User ID :	pb97604	Batch NO. :	VIM2401820
Print Interval :	50000 Tablets	Running Time :	09 Hour 59 Min 08 Sec
Total Counter :	1690220	Total Running Time :	333 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.05	kN	No		
HEP :	25.0 %	13.51	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	11.03	kN	Yes 10	Times	
Ref :		10.81	kN			
LCP :	2.0 %	10.59	kN	Yes 10	Times	
LEP :	25.0 %	8.11	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.75	kN	Min :	0.72	kN	Punch NO.;	32
SD :	1.80	%	Max :	0.78	kN	Punch NO.;	26
Mean Main Pressure :	10.58	kN	Min :	10.06	kN	Punch NO.;	21
SD :	1.90	%	Max :	11.09	kN	Punch NO.;	50
Filling Depth :	Increase ;	18	Times	Decrease ;	22	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.39	mm	Pre Thickness ;	4.89	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.93	mm	Main Thickness ;	1.43	mm
Filling Depth :	5.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.811	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	27	Min			
Lower Punch Remain Time (S2):	39	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	48
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	48
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1690220	Tablets			
A.W.C Counter :	1669603	Tablets			
HEP :	513 (0.0%)	Tablets	LEP :	562 (0.0%)	Tablets
GOOD :	1668528 (99.9%)	Tablets			