

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	pb97604	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	03 Hour 03 Min 14 Sec
Total Counter :	550332	Total Running Time :	346 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.71	kN	No		
HEP :	25.0 %	12.23	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	9.98	kN	Yes	10 Times	
Ref :		9.78	kN			
LCP :	2.0 %	9.59	kN	Yes	10 Times	
LEP :	25.0 %	7.34	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.92	kN	Min :	0.89	kN	Punch NO.;	44
SD :	1.40	%	Max :	0.95	kN	Punch NO.;	61
Mean Main Pressure :	9.80	kN	Min :	9.41	kN	Punch NO.;	33
SD :	1.80	%	Max :	10.19	kN	Punch NO.;	38
Filling Depth :	Increase ;	4	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	4.40	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.53	mm	Current Cam :	Cam B	
Main Air pressure :	0.776	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.09	kN	Max Punch ;	52
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	52
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	550332	Tablets			
A.W.C Counter :	539669	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.1%)	Tablets
GOOD :	539205 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	pb97604	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	03 Hour 03 Min 14 Sec
Total Counter :	550332	Total Running Time :	346 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.33	kN	No		
HEP :	25.0 %	12.81	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.46	kN	Yes	10 Times	
Ref :		10.25	kN			
LCP :	2.0 %	10.05	kN	Yes	10 Times	
LEP :	25.0 %	7.69	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.05	kN	Min :	1.01	kN	Punch NO.;	32
		1.50	%	Max :	1.09	kN	Punch NO.;	35
Mean Main Pressure :		10.23	kN	Min :	9.73	kN	Punch NO.;	23
	SD :	1.90	%	Max :	10.62	kN	Punch NO.;	18
Filling Depth :	Increase ;	5	Times	Decrease ;	13	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.10	mm	Pre Thickness ;	4.60	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.72	mm	Current Cam :	Cam B	
Main Air pressure :	0.776	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.09	kN	Max Punch ;	52
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	52
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	550332	Tablets			
A.W.C Counter :	539669	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.1%)	Tablets
GOOD :	539205 (99.9%)	Tablets			