

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	05 Hour 00 Min 36 Sec
Total Counter :	920820	Total Running Time :	348 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.77	kN	No		
HEP :	25.0 %	12.28	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.02	kN	Yes	10 Times	
Ref :		9.82	kN			
LCP :	2.0 %	9.63	kN	Yes	10 Times	
LEP :	25.0 %	7.37	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.96	kN	Punch NO.;	50
SD :	1.10	%	Max :	1.02	kN	Punch NO.;	48
Mean Main Pressure :	9.86	kN	Min :	9.59	kN	Punch NO.;	9
SD :	1.70	%	Max :	10.31	kN	Punch NO.;	29
Filling Depth :	Increase ;	4	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	4.40	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.60	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.817	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	23
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	41
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	920820	Tablets			
A.W.C Counter :	902624	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.1%)	Tablets
GOOD :	902160 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	05 Hour 00 Min 36 Sec
Total Counter :	920820	Total Running Time :	348 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min : 2.50	mm
Target Quantity :		1740000	Tablets		Max : 8.00	mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.61	kN	No		
HEP :	25.0 %	13.09	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.68	kN	Yes 10	Times	
Ref :		10.47	kN			
LCP :	2.0 %	10.26	kN	Yes 10	Times	
LEP :	25.0 %	7.85	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.33	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.05	kN	Min :	1.03	kN	Punch NO.;	21
		1.10	%	Max :	1.08	kN	Punch NO.;	31
Mean Main Pressure :		10.56	kN	Min :	9.94	kN	Punch NO.;	13
	SD :	2.40	%	Max :	11.24	kN	Punch NO.;	3
Filling Depth :	Increase ;	7	Times	Decrease ;	17	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	156000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.10	mm	Pre Thickness ;	4.60	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.85	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.817	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	30	Min			
Lower Punch Remain Time (S2):	32	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.10	kN	Max Punch ;	23
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	6
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	920820	Tablets			
A.W.C Counter :	902624	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.1%)	Tablets
GOOD :	902160 (99.9%)	Tablets			