

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	06 Hour 29 Min 06 Sec
Total Counter :	1150734	Total Running Time :	349 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	45	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.80	kN	No		
HEP :	25.0 %	12.30	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.04	kN	Yes	10 Times	
Ref :		9.84	kN			
LCP :	2.0 %	9.65	kN	Yes	10 Times	
LEP :	25.0 %	7.38	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.89	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.96	kN	Min :	0.94	kN	Punch NO.;	3
SD :	1.00	%	Max :	0.99	kN	Punch NO.;	49
Mean Main Pressure :	9.77	kN	Min :	9.44	kN	Punch NO.;	9
SD :	1.60	%	Max :	10.24	kN	Punch NO.;	38
Filling Depth :	Increase ;	4	Times	Decrease ;	14	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	6.90	mm	Pre Thickness ;	4.40	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.90	mm	Main Thickness ;	1.40	mm
Filling Depth :	5.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.754	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	22
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1150734	Tablets			
A.W.C Counter :	1132529	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.0%)	Tablets
GOOD :	1132065 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	ACICLO200MG STV11A00
User ID :	ka89411	Batch NO. :	VIM2500120
Print Interval :	50000 Tablets	Running Time :	06 Hour 29 Min 06 Sec
Total Counter :	1150734	Total Running Time :	349 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	73	%	Manual ;	59	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		1740000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.70	kN	No		
HEP :	25.0 %	13.17	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.75	kN	Yes	10 Times	
Ref :		10.53	kN			
LCP :	2.0 %	10.32	kN	Yes	10 Times	
LEP :	25.0 %	7.90	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.37	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.04	kN	Min :	1.01	kN	Punch NO.;	57
		1.40	%	Max :	1.08	kN	Punch NO.;	51
Mean Main Pressure :	SD :	10.45	kN	Min :	9.80	kN	Punch NO.;	13
		2.60	%	Max :	11.20	kN	Punch NO.;	31
Filling Depth :	Increase ;	7	Times	Decrease ;	19	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	7.10	mm	Pre Thickness ;	4.60	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	1.44	mm
Filling Depth :	5.79	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.754	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.10	kN	Max Punch ;	46
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	22
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1150734	Tablets			
A.W.C Counter :	1132529	Tablets			
HEP :	0 (0%)	Tablets	LEP :	464 (0.0%)	Tablets
GOOD :	1132065 (100.0%)	Tablets			